

Product datasheet

Specifications



Electronic overcurrent relay, EOCR Digital, 0.5 to 6A, 220VAC

EOCRSSD-05S

⚠ Discontinued on: 1 Dec 2024

⚠ To be discontinued

Main

Range of product	EOCR
Device short name	EOCR-SSD
Product or component type	Protection relay
Protection type	Overload, $I_n > OC$ setting Sensitivity to phase loss Locked rotor for starting, $I_n > 2$ times OC setting
Product specific application	Overcurrent protection
Network type	AC
Network frequency	50...60 Hz
protection adjustment range	0.5...6 A
Tripping threshold	0.5...6 A

Complementary

[Us] rated supply voltage	220 V AC
Mounting support	35 mm DIN rail Panel
Contacts type and composition	1 NC + 1 NO (OL)
Short-circuit and overload protection	By 4 A gG fuse
[Ue] rated operational voltage	600 V AC 50...60 Hz for power circuit conforming to UL 690 V AC 50...60 Hz for power circuit conforming to CSA 690 V AC 50...60 Hz for power circuit conforming to IEC 60947-4-1
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-4-1
Reset	Manual reset Electrical 0...1 s by interruption of power supply
Time delay type	D-Time: 1...30 s O-Time: 0.5, 1...10 s
Display type	7 segments LED
power consumption per relay	3 W
Connections - terminals	Control circuit: lug-clamp 2 x 1...2.5 mm ² flexible without cable end - M3.5 Control circuit: cable 2 x 1...2.5 mm ² flexible without cable end - M3.5 Control circuit: cable 2 x 1...2.5 mm ² flexible with cable end - M3.5
Tightening torque	Control circuit: 1.7 N.m on lug-clamp, cable, 7 mm
Height	70 mm
Width	56 mm
Depth	77.2 mm

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Product weight	0.255 kg
----------------	----------

Environment

Standards	IEC 60947-4-1
-----------	---------------

IP degree of protection	IP20 conforming to IEC 60529
-------------------------	------------------------------

Ambient air temperature for operation	-20...60 °C conforming to IEC 60947-4-1
---------------------------------------	-----------------------------------------

Ambient air temperature for storage	-30...80 °C
-------------------------------------	-------------

Operating altitude	2000 m
--------------------	--------

Fire resistance	650 °C conforming to IEC 60695-2-12 960 °C conforming to UL 94
-----------------	-------------------------------------------------------------------

Shock resistance	15 gn for 11 ms conforming to IEC 60068-2-7
------------------	---------------------------------------------

Vibration resistance	4 gn on panel mounting conforming to IEC 60068-2-6 2 gn on 35 mm DIN rail conforming to IEC 60068-2-6
----------------------	----------------------------------------------------------------------------------------------------------

Dielectric strength	2 kV 50...60 Hz in between case and circuit conforming to IEC 60255-5 1 kV 50...60 Hz in between contact conforming to IEC 60255-5 2 kV 50...60 Hz in between circuit conforming to IEC 60255-5
---------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Surge withstand	6 kV conforming to IEC 61000-4-5
-----------------	----------------------------------

Electromagnetic compatibility	Resistance to radiated electromagnetic fields: 10 V/m level 3 conforming to IEC 61000-4-3 Resistance to electrostatic discharge: 8 kV air, 6 kV contact conforming to IEC 61000-4-2 Resistance to fast transient: 2 kV conforming to IEC 61000-4-4 Conducted RF disturbances: 10 V conforming to EN 61000-4-6 Conducted RF disturbances: class A conforming to EN 55011
-------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

[Ith] conventional free air thermal current	5 A for control circuit
---------------------------------------------	-------------------------

Permissible current	250 V, 5 A
---------------------	------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	5.9 cm
------------------	--------

Package 1 Width	8.2 cm
-----------------	--------

Package 1 Length	7.9 cm
------------------	--------

Package 1 Weight	196.0 g
------------------	---------

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	94 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	92 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.5 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	92
End of life manual availability	End of Life Information
Take-back	No