

# Product data sheet

Specifications



## ASCO 6110 Load Bank

ASCOLBLV6110

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

### Main

Product Type Resistive load bank

### Complementary

Capacity Rating 300...700 kVA

Capacitance Rating 0.8 pF

Load Step Resolution 1 kW  
1 kvar

Voltage Rating 400 V AC 50 Hz  
415 V AC 50 Hz  
480 V AC 60 Hz

Resistor Load Tolerance 2.5 %

Inductor Load Tolerance 3 %

Cooling System Rating 3708777.9 Gal/hr(US) (14039 m3/h)

Provided Equipment 1 gland plate inside the enclosure  
HRC fuse inside the enclosure  
Voltage transformer 1 inside the enclosure  
Cooling fans inside the enclosure

Connection Terminals Terminals neutral)

IP Protection IP1x  
IP2X  
IP54

Enclosure Material Zintec  
Aluminium  
Steel

Color Gray RAL 7042)

Length 91.3 in (2320 mm)

Width 60.6 in (1540 mm)

Height 75.2 in (1910 mm)

Product Weight 5511.6 lb(US) (2500 kg)

### Environmental

Standards ISO 9001  
CE  
IEC 60309-2

### Contractual warranty

Warranty (in months) 18

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

### Use Longer

#### Lifetime extension

Repair **No**