

Product datasheet

Specifications



integrated drive ILA with servo motor - 24..48 V - Ethernet Powerlink - PCB conn

ILA2P571PB2A0

⚠ Discontinued on: 15 Jun 2023

⚠ To be end-of-service on: 31 Dec 2026

⚠ Discontinued - Service only

Main

| | |
|---------------------------|--|
| Range of product | Lexium integrated drive |
| Product or component type | Motion integrated drive |
| Device short name | ILA |
| Motor type | AC synchronous servo motor |
| Number of motor poles | 6 |
| Network number of phases | Single phase |
| [Us] rated supply voltage | 48 V 24 V |
| Network type | DC |
| Communication interface | Ethernet Powerlink, integrated |
| Length | 189.3 mm |
| Winding type | Medium speed of rotation and medium torque |
| Electrical connection | Printed circuit board connector |
| Holding brake | Without |
| Gear box type | Without |
| Nominal speed | 3200 rpm at 24 V 5100 rpm at 48 V |
| Nominal torque | 0.44 N.m |

Complementary

| | |
|---------------------------------------|--------------------|
| Transmission rate | 100 Mbits |
| Mounting support | Flange |
| Motor flange size | 57 mm |
| Number of motor stacks | 1 |
| Centring collar diameter | 50 mm |
| Centring collar depth | 1.6 mm |
| Number of mounting holes | 4 |
| Mounting holes diameter | 5.2 mm |
| Circle diameter of the mounting holes | 66.6 mm |
| Feedback type | Multi turn encoder |
| Shaft end | Untapped |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

| | |
|-----------------------------------|--|
| Second shaft | Without second shaft end |
| Shaft diameter | 9 mm |
| Shaft length | 20 mm |
| Supply voltage limits | 18...55.2 V |
| Current consumption | 5000 mA maximum continuous 7000 mA peak |
| Associated fuse rating | 16 A |
| Commissioning interface | RS485 Modbus TCP (9.6, 19.2 and 38.4 kbauds) |
| Input/output type | 4 signals (each be used as input or output) |
| Voltage state 0 guaranteed | -3...4.5 V |
| Voltage state 1 guaranteed | 15...30 V |
| Discrete input current | 10 mA at 24 V for safety input 2 mA at 24 V for 24 V signal interface |
| Discrete output voltage | 23...25 V |
| Maximum switching current | 100 mA per output 200 mA total |
| Protection type | Short circuit of the output voltage Safe torque off Overload of output voltage |
| Peak stall torque | 0.62 N.m |
| Continuous stall torque | 0.44 N.m |
| Speed feedback resolution | 16384 points/turn x 4096 turns |
| Accuracy error | +/- 0.05 ° |
| Rotor inertia | 0.095 kg.cm ² |
| Maximum radial force Fr | 89 N |
| Maximum axial force Fa | 104 N (force pressure) 104 N (tensile force) |
| Service life in hours | 20000 h bearing |
| Marking | CE |
| Type of cooling | Natural convection |
| Net weight | 1.4 kg |

Environment

| | |
|--|---|
| Standards | EN 61800-3 : 2001-02 EN 50347 IEC 60072-1 EN/IEC 61800-3 EN/IEC 50178 EN 61800-3:2001, second environment IEC 61800-3, Ed 2 |
| Product certifications | cUL UL TÜV |
| Ambient air temperature for operation | 40...55 °C (with power derating of 2 % per °C) 0...40 °C (without derating) |
| Permissible ambient air temperature around the device | 105 °C power amplifier 110 °C motor |
| Ambient air temperature for storage | -25...70 °C |

| | |
|--------------------------------|---|
| Operating altitude | <= 1000 m without derating |
| Relative humidity | 15...85 % without condensation |
| Vibration resistance | 20 m/s ² (f= 10...500 Hz) 10 cycles conforming to EN/IEC 60068-2-6 |
| Shock resistance | 150 m/s ² 1000 shocks conforming to EN/IEC 60068-2-29 |
| IP degree of protection | IP41 shaft bushing: conforming to EN/IEC 60034-5 IP54 total except shaft bushing: conforming to EN/IEC 60034-5 |

Packing Units

| | |
|-------------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8.0 cm |
| Package 1 Width | 18.5 cm |
| Package 1 Length | 35.5 cm |
| Package 1 Weight | 1.7 kg |

Contractual warranty

| | |
|-----------------------------|----|
| Warranty (in months) | 18 |
|-----------------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better



Materials and Substances

[EU RoHS Directive](#)

Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation

[REACH Declaration](#)

Use Longer



Lifetime extension

Repair

No

Use Again




Repack and remanufacture

End of life manual availability

[End of Life Information](#)


Wiring

Connection Example with 4 I/O Signals



PerformanceCurves

Torque Characteristics



- X Speed of rotation in rpm
- Y Torque in Nm
- 1.1 Max. torque at 24 V
- 1.2 Max. torque at 48 V
- 2 Continuous torque