

Rear horizontal main- connection, TOP or BOTTOM, frame size 2 - 3200A 1 set, 4 pieces for 4 pole 1 set, 4 pieces for 4 pole for circuit breaker in withdrawable design



| Model                                           |                       |
|-------------------------------------------------|-----------------------|
| product brand name                              | SINOVA                |
| number of poles                                 | 4                     |
| size of the circuit-breaker                     | 2                     |
| switching capacity class of the circuit breaker | S                     |
| operational current rated value                 | 3 200 A               |
| accessories                                     | connection technology |
| mounting position                               | on guide frame        |
| Net Weight                                      | 8.712 kg              |
| Approvals Certificates                          |                       |
| General Product Approval                        |                       |



| Further information                                                                                                                                                                                                                                                |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Information on the packaging<br><a href="https://support.industry.siemens.com/cs/ww/en/view/109813875">https://support.industry.siemens.com/cs/ww/en/view/109813875</a>                                                                                            |
| Information for data generation and storage<br><a href="https://support.industry.siemens.com/cs/ww/en/view/109995012">https://support.industry.siemens.com/cs/ww/en/view/109995012</a>                                                                             |
| Information- and Downloadcenter (Catalogs, Brochures,...)<br><a href="https://www.siemens.com/lowvoltage/catalogs">https://www.siemens.com/lowvoltage/catalogs</a>                                                                                                 |
| Industry Mall (Online ordering system)<br><a href="https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WJ9111-0AX26">https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WJ9111-0AX26</a>                                            |
| Service&Support (Manuals, Certificates, Characteristics, FAQs,...)<br><a href="https://support.industry.siemens.com/cs/ww/en/ps/3WJ9111-0AX26">https://support.industry.siemens.com/cs/ww/en/ps/3WJ9111-0AX26</a>                                                  |
| Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)<br><a href="https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WJ9111-0AX26">https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WJ9111-0AX26</a> |
| CAX-Online-Generator<br><a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a>                                                                                                                                                                      |
| Tender specifications<br><a href="https://www.siemens.com/specifications">https://www.siemens.com/specifications</a>                                                                                                                                               |
| Characteristic curves<br><a href='https://curves.simaris.siemens.com/curves/&lt;mmp_prod_noCOMP="HAUPT"&gt;&lt;/mmp_prod_no&gt;'>https://curves.simaris.siemens.com/curves/&lt;mmp_prod_noCOMP="HAUPT"&gt;&lt;/mmp_prod_no&gt;</a>                                 |

