

Product datasheet

Specifications



TeSys K reversing contactor , 3P , AC-3 <= 440 V 6 A , 1 NC , 24 V AC , TQ pkg

LC2K0601B7TQ

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

Main

Range	TeSys
Product name	TeSys K
Product or component type	Reversing contactor
Device short name	LC2K
Device application	Control
Contactors application	Motor control
Utilisation category	AC-3 AC-4
Device presentation	Preassembled with reversing power busbar
Poles description	3P
power pole contact composition	3 NO
[Ue] rated operational voltage	Power circuit: 690 V AC 50/60 Hz Signalling circuit: <= 690 V AC 50/60 Hz
[Ie] rated operational current	6 A at <= 440 V AC AC-3 for power circuit
Motor power kW	1.5 kW at 220...230 V AC 50/60 Hz 2.2 kW at 380...415 V AC 50/60 Hz 3 kW at 440 V AC 50/60 Hz 3 kW at 480 V AC 50/60 Hz 3 kW at 500...600 V AC 50/60 Hz 3 kW at 660...690 V AC 50/60 Hz
Control circuit type	AC at 50/60 Hz
[Uc] control circuit voltage	24 V AC 50/60 Hz
Auxiliary contact composition	1 NC
[Uimp] rated impulse withstand voltage	8 kV
Overvoltage category	III
[Ith] conventional free air thermal current	20 A (at 50 °C) for power circuit 10 A (at 50 °C) for signalling circuit
Irms rated making capacity	110 A AC for power circuit conforming to NF C 63-110 110 A AC for power circuit conforming to IEC 60947 110 A AC for signalling circuit conforming to IEC 60947
Rated breaking capacity	110 A at 415 V conforming to IEC 60947 110 A at 440 V conforming to IEC 60947 80 A at 500 V conforming to IEC 60947 110 A at 220...230 V conforming to IEC 60947 110 A at 380...400 V conforming to IEC 60947 70 A at 660...690 V conforming to IEC 60947

[Icw] rated short-time withstand current	<p>90 A 50 °C - 1 s for power circuit</p> <p>85 A 50 °C - 5 s for power circuit</p> <p>80 A 50 °C - 10 s for power circuit</p> <p>60 A 50 °C - 30 s for power circuit</p> <p>45 A 50 °C - 1 min for power circuit</p> <p>40 A 50 °C - 3 min for power circuit</p> <p>80 A - 1 s for signalling circuit</p> <p>90 A - 500 ms for signalling circuit</p> <p>110 A - 100 ms for signalling circuit</p> <p>20 A 50 °C - >= 15 min for power circuit</p>
Associated fuse rating	<p>25 A gG at <= 440 V for power circuit</p> <p>25 A aM for power circuit</p> <p>10 A gG for signalling circuit conforming to IEC 60947</p> <p>10 A gG for signalling circuit conforming to VDE 0660</p>
Average impedance	3 mOhm - lth 20 A 50 Hz for power circuit
[Ui] rated insulation voltage	<p>Power circuit: 600 V conforming to UL 508</p> <p>Power circuit: 690 V conforming to IEC 60947-4-1</p> <p>Signalling circuit: 690 V conforming to IEC 60947-4-1</p> <p>Signalling circuit: 690 V conforming to IEC 60947-5-1</p> <p>Signalling circuit: 600 V conforming to UL 508</p> <p>Power circuit: 600 V conforming to CSA C22.2 No 14</p> <p>Signalling circuit: 600 V conforming to CSA C22.2 No 14</p>
Electrical durability	1.3 Mcycles 6 A AC-3 at Ue <= 440 V
Interlocking type	Mechanical
Mounting support	<p>Plate</p> <p>Rail</p>
Standards	<p>NF C 63-110</p> <p>IEC 60947</p> <p>VDE 0660</p> <p>BS 5424</p>
Product certifications	<p>CB Scheme</p> <p>CCC</p> <p>UL</p> <p>CSA</p> <p>EAC</p> <p>CE</p> <p>UKCA</p>
Connections - terminals	<p>Screw clamp terminals 1 cable(s) 1.5...4 mm²solid</p> <p>Screw clamp terminals 1 cable(s) 0.75...4 mm²flexible without cable end</p> <p>Screw clamp terminals 1 cable(s) 0.34...2.5 mm²flexible with cable end</p> <p>Screw clamp terminals 2 cable(s) 1.5...4 mm²solid</p> <p>Screw clamp terminals 2 cable(s) 0.75...4 mm²flexible without cable end</p> <p>Screw clamp terminals 2 cable(s) 0.34...1.5 mm²flexible with cable end</p>
Tightening torque	<p>1.3 N.m - on screw clamp terminals - with screwdriver Philips No 2</p> <p>1.3 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm</p>
Operating time	<p>10...20 ms coil energisation and NO closing</p> <p>10...20 ms coil de-energisation and NO opening</p>
Safety reliability level	<p>B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1</p> <p>B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1</p>
Mechanical durability	5 Mcycles
Maximum operating rate	3600 cyc/h
Complementary	
Control circuit voltage limits	<p>Operational: 0.8...1.15 Uc (at <50 °C)</p> <p>Drop-out: 0.2...0.75 Uc (at <50 °C)</p>
Inrush power in VA	30 VA (at 20 °C)
Hold-in power consumption in VA	4.5 VA (at 20 °C)
Heat dissipation	1.3 W
Auxiliary contacts type	type instantaneous 1 NC

Signalling circuit frequency	<= 400 Hz
Minimum switching current	5 mA for signalling circuit
Minimum switching voltage	17 V for signalling circuit
Non overlap distance	0.5 mm
Insulation resistance	> 10 MOhm for signalling circuit

Environment

IP degree of protection	IP20 conforming to VDE 0106
Protective treatment	TC conforming to IEC 60068 TC conforming to DIN 50016
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-50...80 °C
Operating altitude	2000 m without derating
Flame retardance	V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102
Mechanical robustness	Shocks contactor closed, on X axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor closed, on Y axis: 15 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor closed, on Z axis: 15 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on X axis: 6 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on Y axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on Z axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Vibrations contactor closed: 4 Gn, 5...300 Hz conforming to IEC 60068-2-6 Vibrations contactor opened: 2 Gn, 5...300 Hz conforming to IEC 60068-2-6
Height	58 mm
Width	90 mm
Depth	57 mm
Net weight	0.39 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins