
Product datasheet

Specifications



auxiliary contact - NC and NC or SD - for NG125

19073

Discontinued on: 1 Nov 2020

EAN Code: 3303430190738

Discontinued

Main

range of product	Acti9
Product or component type	Double OC or fault contact
Device short name	OF and OF or OF and SD
Signal contacts composition	2 C/O
9 mm pitches	1
Standards	EN/IEC 60947-5-1
Product certifications	ASTA ASEFA KEMA LCIE

Complementary

Range compatibility	Acti9 NG125LMA Acti9 NG125
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to EN/IEC 60947-5-1
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 60947-5-1
Mounting mode	Fixed
Mounting support	DIN rail
Height	102.8 mm
Width	15.3 mm
Depth	75.5 mm
Electrical durability	10000 cycles conforming to EN/IEC 60947-5-1
Connections - terminals	Plate terminal1 cable(s) 2.5 mm² - flexible Plate terminal1 cable(s) 2.5 mm² - rigid Plate terminal2 cable(s) 1.5 mm² - flexible Plate terminal2 cable(s) 1.5 mm² - rigid
Wire stripping length	10 mm
Tightening torque	1 N.m

Environment

Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.5 cm
Package 1 Width	8 cm
Package 1 Length	2.5 cm
Package 1 Weight	0.073 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Longer

Lifetime extension

Repair	No