

# Product data sheet

Specifications



## Multi9 - auxiliary contact - 1 OF - 1NO/NC - 24...415 V AC - 24...130 V DC

MGN26924

⚠ Discontinued on: Jul 2, 2025

⚠ Discontinued

### Main

range of product	Acti9
Product or Component Type	OC contact
Device short name	OF
Signal contacts composition	1 NO/NC
Line Rated Current	3 A at 415 V, AC 50/60 Hz 6 A at <= 240 V, AC 50/60 Hz
[Uc] control circuit voltage	24...130 V DC 24...415 V AC 50/60 Hz
9 mm pitches	1
Standards	EN/IEC 60947-5-1

### Complementary

Range compatibility	Multi9 C60BP Multi9 C60SP Multi9 C60H-DC Acti9 iSW-NA
Mounting Mode	Clip-on
Mounting Support	DIN rail
Height	3.3 in (85 mm)
Width	0.4 in (9 mm)
Depth	2.9 in (73.5 mm)
Net Weight	1.06 oz (30 g)
color	White
Connections - terminals	Clamp terminal bottom) 2 0.002 in <sup>2</sup> (1.5 mm <sup>2</sup> ) - flexible Clamp terminal bottom) 1 0.0008...0.004 in <sup>2</sup> (0.5...2.5 mm <sup>2</sup> ) - rigid Clamp terminal bottom) 2 0.002 in <sup>2</sup> (1.5 mm <sup>2</sup> ) - flexible with ferrule
Wire stripping length	0.4 in (9 mm) for bottom connection
Tightening torque	8.9 lbf.in (1 N.m) bottom

### Environment

Ambient Air Temperature for Operation	-13...140 °F (-25...60 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)

### Ordering and shipping details

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

GTIN 3606480545160

## Packing Units

---

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.9 in (2.2 cm)
Package 1 Width	3.1 in (8 cm)
Package 1 Length	3.7 in (9.4 cm)
Package weight(Lbs)	1.3 oz (38 g)

---

## Contractual warranty

---

Warranty (in months)	18
----------------------	----

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

Packaging made with recycled cardboard

Yes

[EU RoHS Directive](#)

Compliant

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.