

Product data sheet

Specifications



Detached triple servo drive 2,7A continuous current, 24A peak, IP65

ILM62DDD24B1000

Main

Range of product	PacDrive 3
Product or component type	Detached servo drive
Device short name	ILD

Complementary

Product compatibility	Servo motor MH3 Motor asynchronous motor Servo motor SH3 2.7 A
[Us] rated supply voltage	250...700 V
[In] rated current	2.7 A natural convection
Safety function	STO (safe torque off)
Type of cooling	Fanless Natural convection
Number of mounting holes	4
Net weight	11.7 lb(US) (5.3 kg)

Environment

IP degree of protection	IP65
Standards	IEC 61800-5-2 IEC 61800-5-1 UL 618000-5-1 CSA C22.2 No 274 IEC 61800-3 ISO 13849-1 IEC 62061
Directives	2014/35/EU - low voltage directive 2006/42/EC - machinery 2014/30/EU - electromagnetic compatibility
Product certifications	cULus CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.283 in (18.500 cm)
Package 1 Width	18.425 in (46.800 cm)
Package 1 Length	13.386 in (34.000 cm)
Package 1 Weight	14.237 lb(US) (6.458 kg)

Contractual warranty

Warranty (in months)

18



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Take-back

No