



SIMATIC CN 4100, expansion module serial RS232, communications processor, supports the data exchange with third-party systems via 4x RS232 interface

General information	
Product type designation	serial RS232 expansion module
Engineering with	
• PCS 7 configurable/integrated from version	V9.0 SP3
• CNET can be configured/integrated as of version	V2.0
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption, typ.	350 mA
Current consumption, max.	500 mA
Power loss	
Power loss, typ.	9 W
Power loss, max.	12 W
Hardware configuration	
Slots	
• required slots	1
Interfaces	
Number of RS 485 interfaces	4
Protocols	
Modbus RTU	Yes
Standards, approvals, certificates	
CE mark	Yes
UKCA mark	Yes
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-30 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-30 °C
• vertical installation, max.	45 °C
Software	
Pre-installed software	none
Dimensions	
Width	45 mm
Height	185 mm
Depth	112 mm
Weights	
Weight, approx.	0.42 kg
Classifications	

	Version	Classification
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423

Approvals / Certificates

General Product Approval	other
--------------------------	-------



[Miscellaneous](#)

last modified:

6/7/2025