

Product datasheet

Specifications



servo motor BCH16, Lexium 16D,
100mm, shaft 22mm, 1.0kW, Low
inertia, 3000rpm, 23bit

BCH16LJ10332A6C2

⚠ Discontinued on: 27 Sept 2022

⚠ Discontinued

Main

Range compatibility	Easy Lexium 16
Device short name	BCH16
Product or component type	Servo motor

Complementary

Maximum mechanical speed	5000 rpm
[Us] rated supply voltage	220 V
Network number of phases	3 phases
Continuous stall current	6.6 A
Continuous stall torque	3.18 N.m for LXM16D at 10.13 A, 220 V, single phase
Continuous power	1000 W
Peak stall torque	9.55 N.m for LXM16D at 10.13 A, 220 V, single phase
Nominal output power	1000 W for LXM16D at 10.13 A, 220 V, single phase
Nominal torque	3.18 N.m for LXM16D at 10.13 A, 220 V, single phase
Nominal speed	3000 rpm for LXM16D at 10.13 A, 220 V, single phase
Maximum current Irms	21.9 A for LXM16D at 1.0 kW, 220 V
Maximum permanent current	21.8 A
Product compatibility	LXM16D motion servo motors motor at 1 kW, 220 V, single phase
Shaft end	Parallel key
Second shaft	Without second shaft end
Shaft diameter	22 mm
Shaft length	35 mm
Key width	8 mm
Feedback type	23 bit high resolution encoder
Holding brake	Without
Holding torque	6.5 N.m
Mounting support	Asian standard flange
Motor flange size	100 mm
Electrical connection	Connector MIL
Torque constant	0.48 N.m/A at 20 °C

Back emf constant	32 V/krpm at 20 °C
Rotor inertia	2.65 kg.cm ²
Stator resistance	0.7 Ohm at 20 °C
Stator inductance	4.3 mH at 20 °C
Stator electrical time constant	6.14 ms at 20 °C
Maximum radial force Fr	343.98 N at 3000 rpm
Maximum axial force Fa	122.3 N
Type of cooling	Natural convection
Length	139 mm
Centring collar diameter	95 mm
Centring collar depth	3 mm
Number of mounting holes	4
Mounting holes diameter	9 mm
Circle diameter of the mounting holes	115 mm
Distance shaft shoulder-flange	50 mm
Width	100 mm
Height	153.4 mm
Depth	139 mm
Net weight	3.8 kg

Environment

IP degree of protection	IP65 IM B5, IM V1 IP65 IM V3
Ambient air temperature for operation	0...40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.5 cm
Package 1 Width	18 cm
Package 1 Length	36 cm
Package 1 Weight	4.16 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better



Materials and Substances

[EU RoHS Directive](#)

Compliant with Exemptions

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

[End of life manual availability](#)

[End of Life Information](#)

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins