


Product data sheet

Specifications



standard early break contact,
ComPact NSX100 to NSX250,
rotary handle position CAO, 1
changeover contact type

LV429345

! Discontinued

Main

Range of Product	ComPact NSX100...250 ComPact NSX100...250 DC
Range	ComPact
Device short name	early-break contact
Product or Component Type	Auxiliary contact
Device Application	Control
Range compatibility	ComPact ComPact NSX100 ComPact ComPact NSX160 ComPact ComPact NSX250 ComPact Compact NSX100 DC ComPact Compact NSX160 DC ComPact Compact NSX250 DC PowerPact PowerPact H PowerPact PowerPact J

Complementary

Auxiliary contacts type	Standard
Auxiliary contacts operation	Early-break
Mounting Mode	Drawout
[Ith] conventional free air thermal current	6 A
[Ie] rated operational current	AC-12 6 A 110 V AC 50/60 Hz AC-12 6 A 220/240 V AC 50/60 Hz AC-12 6 A 24 V AC 50/60 Hz AC-12 6 A 380/440 V AC 50/60 Hz AC-12 6 A 48 V AC 50/60 Hz AC-12 6 A 480 V AC 50/60 Hz AC-12 6 A 660/690 V AC 50/60 Hz AC-15 0.1 A 660/690 V AC 50/60 Hz AC-15 1.5 A 480 V AC 50/60 Hz AC-15 2 A 380/440 V AC 50/60 Hz AC-15 4 A 220/240 V AC 50/60 Hz AC-15 5 A 110 V AC 50/60 Hz AC-15 6 A 24 V AC 50/60 Hz AC-15 6 A 48 V AC 50/60 Hz DC-12 0.3 A 250 V DC DC-12 0.6 A 110 V DC DC-12 2.5 A 48 V DC DC-12 6 A 24 V DC DC-14 0.03 A 250 V DC DC-14 0.05 A 110 V DC DC-14 0.2 A 48 V DC DC-14 1 A 24 V DC
Minimum load	100 mA 24 V DC

Ordering and shipping details

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Category	01081-INTRA-COMPANY COMPONENTS
Discount Schedule	NET
GTIN	3606480020438
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.6 in (4.0 cm)
Package 1 Width	2.4 in (6.2 cm)
Package 1 Length	3.1 in (8.0 cm)
Package weight(Lbs)	1.7 oz (49.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	45
Package 2 Height	11.8 in (30.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	5.538 lb(US) (2.512 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	312689d4-b5e9-4f97-8a29-60feec92eae5
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.