



Connection components (continued)						
Control cordsets						
Description	From servo motor	To servo drive	Composition	Length	Reference	Weight
				m/ft		kg/lb
SinCos Hiperface® encoder cordsets equipped with an M23 industrial connector (servo motor end) and an RJ45 connector with 8+2 contacts (servo drive end)	BSH●●●●●	LXM32●●●●● See references pages 8 and 9	[3 x (2 x 0.14 mm ² / AWG 26) + (2 x 0.34 mm ² / AWG 22)]	1.5/ 4.92	VW3M8102R15	0.400/ 0.882
				3/ 9.84	VW3M8102R30	0.500/ 1.102
				5/ 16.40	VW3M8102R50	0.600/ 1.323
				10/ 32.81	VW3M8102R100	0.900/ 1.984
				15/ 49.21	VW3M8102R150	1.100/ 2.425
				20/ 65.62	VW3M8102R200	1.400/ 3.086
				25/ 82.02	VW3M8102R250	1.700/ 3.748
				50/ 164.04	VW3M8102R500	3.100/ 6.834
SinCos Hiperface® encoder cordsets equipped with an ytec industrial connector (servo motor end) and an RJ45 connector with 8+2 contacts (servo drive end)	BSH040●P●●	LXM32●●●●● See references pages 8 and 9	[3 x (2 x 0.14 mm ² / AWG 26) + (2 x 0.34 mm ² / AWG 22)]	3/9.84	VW3M8100R30	0.500/ 1.102
				5/16.40	VW3M8100R50	0.600/ 1.323
				10/32.81	VW3M8100R100	0.900/ 1.984
				15/49.21	VW3M8100R150	1.100/ 2.425
				25/82.02	VW3M8100R250	1.700/ 3.748