

Product datasheet

Specifications



front connection upside horizontal mounting, MasterPact NT08/NT20, fixed, 4 poles

34106

Main

Range of product	MasterPact NT UL 489
Product or component type	Front connection
Accessory / separate part category	Connection accessory
Range compatibility	Masterpact MasterPact NT UL 489 MasterPact NT08 circuit breaker Masterpact MasterPact NT UL 489 MasterPact NT10 circuit breaker Masterpact MasterPact NT UL 489 MasterPact NT12 circuit breaker
Poles description	4P
Mounting mode	Fixed
[In] rated current	800...2000 A

Complementary

Location of connection	Front
Localisation on device	Upside
Connection pitch	70 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	8.0 cm
Package 1 Length	20.0 cm
Package 1 Weight	1.7 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Free of Substances of Very High Concern above the threshold](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Take-back

No