

Product datasheet

Specifications



extra neutral bar for distribution terminal block - 125 A

13518

⚠ Discontinued on: 6 May 2019

⚠ Discontinued

Main

Range of product	Canalis KV Prisma P Prisma PH Prisma GX Prisma G
Product or component type	Extension module
Comb busbar, distribution terminal block accessory type	Neutral bar
Poles description	1N
Accessory / separate part category	Connection accessories

Complementary

Distribution block outgoers	4 x 17 holes
Mounting support	Multifix rail 35 mm symmetrical DIN rail
[Ie] rated operational current	125 A
[Ui] rated insulation voltage	500 V AC
[Icw] rated short-time withstand current	3.5 kA for 1 s
[Ipk] rated peak withstand current	20 kA
Busbar length	134 mm
Kit composition	Insulating back Cover Open screws
Connections - terminals	Cable 6...16 mm² semi-rigid
Product compatibility	Pragma F24 modular enclosures Prisma functional enclosures Pragma D18 modular enclosures All enclosures Pragma C12 modular enclosures

Environment

Standards	EN 60947-7-1
Pollution degree	3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Height	0.6 cm
Package 1 Width	0.9 cm
Package 1 Length	12.6 cm
Package 1 Weight	0.055 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins