

Product data sheet

Specifications



MH3 servomotor, 100mm, 3 stacks, keyed Shaft, SinCos Multiturn 16, no Brake, angular, IP65

MH31003P17A2200

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range Compatibility	PacDrive 3
Device short name	MH3
Product or Component Type	Servo motor

Complementary

Maximum mechanical speed	6000 rpm
[Us] rated supply voltage	115...480 V
Phase	Three phase
Continuous stall current	7.69 A
Continuous stall torque	79.7 lbf.in (9 N.m), 115...480 V, three phase
Continuous power	3270 W
Peak stall torque	239.0 lbf.in (27 N.m), 115...480 V, three phase
Nominal output power	0.88 W, 115 V 2 W, 230 V 2.85 W, 400 V 3.27 W, 480 V
Nominal torque	74.79 lbf.in (8.45 N.m) LXM52 7.3 mA, 115 V, three phase 67.53 lbf.in (7.63 N.m) LXM52 6.7 mA, 230 V, single phase 60.2 lbf.in (6.8 N.m) LXM52 6.07 mA, 400 V, three phase 55.32 lbf.in (6.25 N.m) LXM52 5.64 mA, 480 V, three phase 74.79 lbf.in (8.45 N.m) LXM62 7.3 mA, 115 V, single phase 67.53 lbf.in (7.63 N.m) LXM62 6.7 mA, 230 V, single phase 60.2 lbf.in (6.8 N.m) LXM62 6.07 mA, 400 V, three phase 55.32 lbf.in (6.25 N.m) LXM62 5.64 mA, 480 V, three phase
Nominal speed	1000 rpm LXM52 7.3 mA, 115 V, single phase 2500 rpm LXM52 6.7 mA, 230 V, single phase 4000 rpm LXM52 6.07 mA, 400 V, three phase 5000 rpm LXM52 5.64 mA, 480 V, three phase 1000 rpm LXM62 7.3 mA, 115 V, single phase 2500 rpm LXM62 6.7 mA, 230 V, single phase 4000 rpm LXM62 6.07 mA, 400 V, three phase 5000 rpm LXM62 5.64 mA, 480 V, three phase
Maximum current Irms	26.71 A
Shaft end	Parallel key
Second shaft	Without second shaft end
Shaft diameter	0.7 in (19 mm)
Shaft length	1.6 in (40 mm)
Key width	0.2 in (6 mm)
IP Degree of Protection	IP65 standard
Encoder type	Multiturn SinCos Hiperface

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Speed feedback resolution	16 periods
Holding brake	Without
Mounting Support	International standard flange
Motor flange size	3.9 in (100 mm)
Electrical Connection	Rotatable right-angled connectors
Torque constant	1.17 N.m/A 248 °F (120 °C)
Back emf constant	77.95 V/krpm
Number of motor poles	5.0
Rotor inertia	10.3 kg.cm²
Stator resistance	1.08 Ohm
Stator inductance	5.23 mH
Stator electrical time constant	6.3 ms
Maximum radial force Fr	1050 N 1000 rpm 830 N 2000 rpm 730 N 3000 rpm 660 N 4000 rpm 610 N 5000 rpm
Type of cooling	Natural convection
Length	7.6 in (192.6 mm)
Centring collar diameter	3.7 in (95 mm)
Centring collar depth	0.1 in (3.5 mm)
Number of mounting holes	4
Mounting holes diameter	0.4 in (9 mm)
Circle diameter of the mounting holes	4.5 in (115 mm)
Net Weight	14.3 lb(US) (6.5 kg)
Sizing reference	MH31003P
Temperature copper hot	275 °F (135 °C)
Output current 3s peak	26.71 A
Inertia	0.0 kg.cm² of brake 9.37 kg.cm² of motor
Nominal speed	4000 rpm

Ordering and shipping details

Category	US1PC5218359
Discount Schedule	PC52
GTIN	3606485396668
Returnability	Yes
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	8.3 in (21.0 cm)

Package 1 Width	7.09 in (18.0 cm)
Package 1 Length	14.02 in (35.6 cm)
Package weight(Lbs)	16.42 lb(US) (7.45 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	3 221 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	54 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	3 165 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.6 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No