

# Product data sheet

Specifications



## contactor - TeSys Deca - 4 poles - AC-1 440V 60 A - coil 380 V AC

LC1D40004Q5

⚠ Discontinued

### Main

Range of Product	TeSys Deca
Product or Component Type	Contactor
Device short name	LC1D
Contactor application	Resistive load
Utilisation category	AC-1 AC-3 AC-3e AC-4
Poles description	4P
[Ue] rated operational voltage	Power circuit <= 690 V AC 25...400 Hz
[Ie] rated operational current	60 A (at <140 °F (60 °C)) AC AC-1 for power circuit
[Uc] control circuit voltage	380 V AC 50 Hz

### Complementary

Compatibility code	LC1D
Pole contact composition	4 NO
Protective cover	With
[Ith] conventional free air thermal current	10 A (at 140 °F (60 °C)) for control circuit 60 A (at 140 °F (60 °C)) for power circuit
Irms rated making capacity	140 A AC for control circuit conforming to IEC 60947-5-1 800 A at 440 V for power circuit conforming to IEC 60947
Rated breaking capacity	800 A at 440 V for power circuit conforming to IEC 60947
Associated fuse rating	10 A gG for control circuit conforming to IEC 60947-5-1 80 A gG at <= 690 V coordination type 1 for power circuit 80 A gG at <= 690 V coordination type 2 for power circuit
Average impedance	1.5 mOhm - Ith 60 A 50 Hz for power circuit
Power dissipation per pole	5.4 W AC-1
[Ui] rated insulation voltage	Control circuit 600 V CSA Control circuit 600 V UL Power circuit 600 V CSA Power circuit 600 V UL Control circuit 690 V IEC 60947-1 Power circuit 690 V IEC 60947-1
Overvoltage category	III
[Uimp] rated impulse withstand voltage	6 kV IEC 60947
Safety reliability level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Mechanical durability</b>	6000000 cycles
<b>Control circuit type</b>	AC 50 Hz standard
<b>Coil technology</b>	Without built-in bidirectional peak limiting diode suppressor
<b>Control circuit voltage limits</b>	0.3...0.6 U <sub>c</sub> (140 °F (60 °C)):drop-out AC 50 Hz 0.85...1.1 U <sub>c</sub> (131 °F (55 °C)):operational AC 50 Hz
<b>Inrush power in VA</b>	140 VA cos phi 0.75 (at 68 °F (20 °C)) 160 VA cos phi 0.75 (at 68 °F (20 °C))
<b>Hold-in power consumption in VA</b>	13 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 15 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))
<b>Heat dissipation</b>	4...5 W at 50/60 Hz for control circuit
<b>Operating time</b>	12...26 ms closing 4...19 ms opening
<b>Maximum operating rate</b>	3600 cyc/h 140 °F (60 °C)
<b>Connections - terminals</b>	Control circuit: screw clamp terminal 1 0.002...0.006 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: solid without cable end Control circuit: screw clamp terminal 2 0.002...0.004 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) - cable stiffness: flexible with cable end Control circuit: screw clamp terminal 2 0.002...0.006 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: flexible without cable end Control circuit: screw clamp terminal 2 0.002...0.006 in <sup>2</sup> (1...4 mm <sup>2</sup> ) - cable stiffness: solid without cable end Power circuit: screw clamp terminal 1 0.002...0.05 in <sup>2</sup> (1...35 mm <sup>2</sup> ) - cable stiffness: solid without cable end Power circuit: screw clamp terminal 2 0.002...0.04 in <sup>2</sup> (1...25 mm <sup>2</sup> ) - cable stiffness: solid without cable end Power circuit: screw clamp terminal 2 0.002...0.05 in <sup>2</sup> (1...35 mm <sup>2</sup> ) - cable stiffness: solid without cable end
<b>Tightening torque</b>	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminal flat Ø 6 mm Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminal Philips No 2 Power circuit 44.3 lbf.in (5 N.m) screw clamp terminal flat Ø 6 mm Power circuit 44.3 lbf.in (5 N.m) screw clamp terminal flat Ø 8 mm Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminal pozidriv No 2
<b>Auxiliary contacts type</b>	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1
<b>Minimum switching voltage</b>	17 V for control circuit
<b>Minimum switching current</b>	5 mA for control circuit
<b>Insulation resistance</b>	> 10 MOhm for control circuit
<b>Non-overlap time</b>	1.5 ms on de-energisation between NC and NO contacts 1.5 ms on energisation between NC and NO contacts
<b>Mounting Support</b>	Plate Rail
<b>Environment</b>	
<b>Standards</b>	EN 60947-5-1 IEC 60947-4-1 UL 508 EN 60947-4-1 IEC 60947-5-1 CSA C22.2 No 14
<b>Product Certifications</b>	UL CSA RINA CCC LROS (Lloyds register of shipping) GL DNV BV GOST
<b>IP degree of protection</b>	IP2X IEC 60529 IP2X VDE 0106

<b>Protective treatment</b>	TH 3)IEC 60068
<b>Permissible ambient air temperature around the device</b>	-76...176 °F (-60...80 °C) storage -40...140 °F (-40...60 °C) operation 140...158 °F (60...70 °C) with derating
<b>Operating altitude</b>	9842.52 ft (3000 m) without derating
<b>Fire resistance</b>	1562 °F (850 °C) IEC 60695-2-1
<b>Flame retardance</b>	V1 conforming to UL 94
<b>Mechanical robustness</b>	Shocks contactor closed 8 gn) Shocks contactor opened Vibrations contactor opened Vibrations contactor closed
<b>Height</b>	5 in (127 mm)
<b>Width</b>	3.3 in (85 mm)
<b>Depth</b>	4.9 in (125 mm)
<b>Net Weight</b>	3.17 lb(US) (1.44 kg)

## Ordering and shipping details

<b>Category</b>	22357-CTR, TESYS D, OPEN, 40-65A AC
<b>Discount Schedule</b>	I12
<b>GTIN</b>	3389110069693
<b>Returnability</b>	No
<b>Country of origin</b>	CZ

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.