

Product data sheet

Specifications



ASCO 3066 Load Bank

ASCOLBLV3066

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Resistive load bank

Complementary

Voltage Rating
380 V AC 50 Hz
400 V AC 50 Hz
415 V AC 50 Hz
440 V AC 60 Hz
480 V AC 60 Hz

Capacity Rating
600 kW
635 kW
665 kW
680 kW

Load Step Resolution 1 kW

Cooling System Rating 6181419.7 Gal/hr(US) (23398.8 m3/h)

Provided Equipment
1 gland plate
Cooling fans

Enclosure Material Zintec

Surface Finish Zinc plated

Color Gray RAL 7042)

Connection Terminals Terminals inside)

Length 80.3 in (2040 mm)

Width 60.6 in (1540 mm)

Height 57.9 in (1470 mm)

Product Weight 1851.9 lb(US) (840 kg)

Environment

Ambient Air Temperature 95 °F (35 °C)

Standards
ISO 9001
CE

IP Protection
IP1x
IP54

Packing Units

Unit Type of Package 1 PCE

Nbr. of units in pkg. 1

Package 1 Height 80.3 in (204.0 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Width	60.6 in (154.0 cm)
Package 1 Length	57.9 in (147.0 cm)
Package weight(Lbs)	1851.9 lb(US) (840.0 kg)

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	No
--------------------------------------	----

Use Longer



Lifetime extension

Repair	No
--------	----