



Figure similar

SIRIUS MCU motor starter Enclosure degree of protection IP54 metal
Communication AS-Interface electromechanically switching Short-circuit protection
with circuit breaker DOL starter Brake 400 V AC (internal) Performance class 4.00
A Motor circuit breaker with bi-metal thermal Rotary operating mechanism
gray/black Connection power M screw connection Standard product

product brand name	SIRIUS
product designation	motor starter MCU for AS-Interface
design of the product	direct starter
product function bus communication	Yes
operating frequency minimum	80 1/h
type of coordination	1
reference code according to IEC 81346-2	Q
Substance Prohibitance (day/month/year)	05/01/2012
SVHC substance name	Lead monoxide (lead oxide) CAS-No. 1317-36-8 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one CAS-No. 71868-10-5 Melamine CAS-No. 108-78-1 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol CAS-No. 119-47-1
Net Weight	6.151 kg
product component motor brake output	Yes
product feature	• brake control with 400 V AC Yes • brake control with 24 V DC No • brake control with 180 V DC No • brake control with 500 V DC No
product extension braking module for brake control	No
design of short-circuit protection	circuit-breakers
maximum short-circuit current breaking capacity (Icu) at 400 V rated value	50 000 A
Safety related data	
proportion of dangerous failures	• with low demand rate according to SN 31920 50 % • with high demand rate according to SN 31920 75 %
B10 value with high demand rate according to SN 31920	1 000 000
failure rate [FIT] with low demand rate according to SN 31920	100 FIT
IEC 61508	
T1 value for proof test interval or service life according to IEC 61508	20 a
Electrical Safety	
touch protection against electrical shock	finger-safe
Main circuit	
number of poles for main current circuit	3
design of the switching contact	electromechanical
adjustable current response value current of the current-	2.8 ... 4 A

dependent overload release				
type of the motor protection			bimetal	
type of voltage			DC	
operating voltage rated value			340 ... 440 V	
operating frequency 1 rated value			50 Hz	
operating frequency 2 rated value			60 Hz	
relative positive tolerance of the operating frequency			10 %	
relative negative tolerance of the operating frequency			-10 %	
operational current				
• at AC at 400 V rated value			4 A	
• at AC-3 at 400 V rated value			4 A	
operating power at AC-3 at 400 V rated value			1.5 kW	
operating power for 3-phase motors at 400 V at 50 Hz			1.5 kW	
number of digital inputs			2	
type of voltage of the supply voltage			DC	
control supply voltage at DC rated value			20.4 ... 26.4 V	
mounting position			+/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface	
height			215 mm	
width			245 mm	
depth			205 mm	
Ambient conditions				
ambient temperature during operation			-25 ... +50 °C	
protocol is supported				
• PROFIBUS DP protocol			No	
• PROFINET protocol			No	
protocol is supported AS-Interface protocol			Yes	
type of electrical connection for main current circuit			screw-type terminals	
Approvals Certificates				
General Product Ap- proval	Test Certificates	other	Dangerous goods	Environment



[Type Test Certificates/Test Report](#)

[Confirmation](#)



[Transport Information](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK4320-3JQ54-0BA3>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK4320-3JQ54-0BA3>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK4320-3JQ54-0BA3>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK4320-3JQ54-0BA3&lang=en

Characteristic curves

https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>

last modified:

9/18/2025