

Product datasheet

Specifications



TeSys F magnetic latching contactor - 3P - 150 A - 220 V/24 V AC/DC coil

CR1F150MB7

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

Main

Range	TeSys
Product name	TeSys F
Product or component type	Magnetic latching contactor
Device short name	CR1F
Device application	Control
Contactor application	Resistive load Motor control
Utilisation category	AC-4 AC-1 AC-3
Poles description	3P
power pole contact composition	3 NO
[Ue] rated operational voltage	1000 V AC 25...200 Hz
[Ie] rated operational current	150 A (at <40 °C) at <= 440 V AC AC-3 250 A (at <40 °C) at <= 440 V AC AC-1 138 A (at <40 °C) at <= 440 V AC AC-4
Motor power kW	65 kW at 1000 V AC 50/60 Hz 100 kW at 690 V AC 50/60 Hz 90 kW at 500...660 V AC 50/60 Hz 80 kW at 440 V AC 50/60 Hz 80 kW at 415 V AC 50/60 Hz 75 kW at 380...400 V AC 50/60 Hz 40 kW at 220...230 V AC 50/60 Hz
motor power HP (UL / CSA)	125 hp at 575...600 V AC 50/60 Hz for 3 phases motors 100 hp at 460...480 V AC 50/60 Hz for 3 phases motors 50 hp at 220...240 V AC 50/60 Hz for 3 phases motors 40 hp at 200...208 V AC 50/60 Hz for 3 phases motors
[Uc] control circuit voltage	220 V AC 50/60 Hz special latching 220 V AC 400 Hz special latching 220 V DC special latching 24 V AC 50/60 Hz special unlatching 24 V AC 400 Hz special unlatching 24 V DC special unlatching
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	250 A (at 40 °C)
Irms rated making capacity	1700 A
Rated breaking capacity	1500 A at 220...440 V 1200 A at 500 V 450 A at 1000 V 1100 A at 660/690 V

[Icw] rated short-time withstand current	1200 A 40 °C - 1 s 1200 A 40 °C - 5 s 1200 A 40 °C - 10 s 700 A 40 °C - 30 s 600 A 40 °C - 1 min 450 A 40 °C - 3 min 350 A 40 °C - 10 min
Associated fuse rating	160 A aM at <= 440 V 250 A BS88 at <= 440 V 250 A gG at <= 440 V
Average impedance	0.45 mOhm - Ith 250 A 50 Hz
[Ui] rated insulation voltage	1000 V conforming to IEC 60158-1 1000 V conforming to IEC 60947-4 1000 V conforming to BS 775 1500 V conforming to VDE 0110 group C
Power dissipation per pole	6 W AC-3 18 W AC-1
Connections - terminals	Lugs-ring terminals 1 cable(s) 120 mm ² Connector 1 cable(s) 120 mm ² Bars 2 cable(s) - busbar cross section: 25 x 3 mm
Tightening torque	18 N.m
Operating time	35...40 ms latching 50...100 ms unlatching
Mechanical durability	1 Mcycles
Maximum operating rate	120 cyc/h 40 °C

Complementary

Control circuit voltage limits	Latching: 0.85...1.1 Uc Unlatching: 0.85...1.1 Uc
average consumption	1100 VA AC 50/60 Hz latching 7.3 VA AC 50/60 Hz unlatching 1260 VA AC 400 Hz latching 1260 W DC latching 10 VA AC 400 Hz unlatching 10 W DC unlatching

Environment

Protective treatment	TH
Ambient air temperature for operation	-15...70 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without derating
Height	170 mm
Width	163.5 mm
Depth	171 mm
Net weight	3.5 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No