

# Product data sheet

Specifications



## ASCO 6067 Load Bank

ASCOLBLV6067

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

### Main

Product Type Resistive load bank

### Complementary

Max Capacity Rating 400 kvar

Capacitance Rating 0.8 pF

Load Step Resolution 1 kW  
1 kvar

Voltage Rating 380...690 V AC 50/60 Hz

Inductor Load Tolerance 3 %

Provided Equipment 1 gland plate inside the enclosure  
HRC fuse inside the enclosure  
Voltage transformer 1 inside the enclosure  
Cooling fans inside the enclosure

Connection Terminals Terminals neutral)

IP Protection IP2X  
IP54

Enclosure Material Zintec  
Aluminium  
Steel

Color Gray RAL 7042)

Length 80.3 in (2040 mm)

Width 60.6 in (1540 mm)

Height 57.9 in (1470 mm)

Product Weight 3924.2 lb(US) (1780 kg)

### Environmental

Standards ISO 9001  
CE  
IEC 60309-2

### Packing Units

Unit Type of Package 1 PCE

Nbr. of units in pkg. 1

Package 1 Height 80.3 in (204.0 cm)

Package 1 Width 60.6 in (154.0 cm)

Package 1 Length 57.9 in (147.0 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Package weight(Lbs) 3924.2 lb(US) (1780.0 kg)

## Contractual warranty

---

Warranty (in months) 18



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	No
--------------------------------------	----

### Use Longer



#### Lifetime extension

Repair	No
--------	----