


H-Frame, J-Frame unit-mount circuit breaker

PowerPact H-Frame 150 A unit-mount thermal-magnetic circuit breakers (480 V AC, 250 V DC)

With factory sealed trip unit (suitable for reverse connection)



H-Frame, 150 A, 3P, 480 V AC 50/60 Hz, 250 V DC - bus bar connectors (with metric terminal nut)


Current rating at 40 °C (A)	Fixed AC magnetic trip (A)		Interrupting rating Standard (80 %) rated		
	Hold	Trip	D - 18 kA	G - 35 kA	J ⁽¹⁾ - 65 kA
15	350	750	NHDF36015TW	NHGF36015TW	NHJF36015TW
20	350	750	NHDF36020TW	NHGF36020TW	NHJF36020TW
30	350	750	NHDF36030TW	NHGF36030TW	NHJF36030TW
40	400	850	NHDF36040TW	NHGF36040TW	NHJF36040TW
50	400	850	NHDF36050TW	NHGF36050TW	NHJF36050TW
60	800	1450	NHDF36060TW	NHGF36060TW	NHJF36060TW
70	800	1450	NHDF36070TW	NHGF36070TW	NHJF36070TW
80	800	1450	NHDF36080TW	NHGF36080TW	NHJF36080TW
90	800	1450	NHDF36090TW	NHGF36090TW	NHJF36090TW
100	900	1700	NHDF36100TW	NHGF36100TW	NHJF36100TW
125	900	1700	NHDF36125TW	NHGF36125TW	NHJF36125TW
150	900	1700	NHDF36150TW	NHGF36150TW	NHJF36150TW

H-Frame, 150 A, 3P, 480 V AC 50/60 Hz, 250 V DC - lug lug connectors

Current rating at 40 °C (A)	Fixed AC magnetic trip (A)		Interrupting rating Standard (80 %) rated		
	Hold	Trip	D - 18 kA	G - 35 kA	J ⁽¹⁾ - 65 kA
15	350	750	NHDL36015	NHGL36015	NHJL36015
20	350	750	NHDL36020	NHGL36020	NHJL36020
30	350	750	NHDL36030	NHGL36030	NHJL36030
40	400	850	NHDL36040	NHGL36040	NHJL36040
50	400	850	NHDL36050	NHGL36050	NHJL36050
60	800	1450	NHDL36060	NHGL36060	NHJL36060
70	800	1450	NHDL36070	NHGL36070	NHJL36070
80	800	1450	NHDL36080	NHGL36080	NHJL36080
90	800	1450	NHDL36090	NHGL36090	NHJL36090
100	900	1700	NHDL36100	NHGL36100	NHJL36100
125	900	1700	NHDL36125	NHGL36125	NHJL36125
150	900	1700	NHDL36150	NHGL36150	NHJL36150

PowerPact J-Frame 250 A unit-mount thermal-magnetic circuit breakers

With factory sealed trip unit (suitable for reverse connection)



J-Frame, 250 A, 3P, 480 V AC 50/60 Hz, 250 V DC - bus bar connectors (with metric terminal nut)

Current rating at 40 °C (A)	Fixed AC magnetic trip (A)		Interrupting rating Standard (80 %) rated		
	Hold	Trip	D - 18 kA	G - 35 kA	J ⁽¹⁾ - 65 kA
150	750	1500	NJDF36150TW	NJGF36150TW	NJJF36150TW
175	875	1750	NJDF36175TW	NJGF36175TW	NJJF36175TW
200	1000	2000	NJDF36200TW	NJGF36200TW	NJJF36200TW
225	1125	2250	NJDF36225TW	NJGF36225TW	NJJF36225TW
250	1250	2500	NJDF36250TW	NJGF36250TW	NJJF36250TW

J-Frame, 250 A, 3P, 480 V AC 50/60 Hz, 250 V DC - lug lug connectors

Current rating at 40 °C (A)	Fixed AC magnetic trip (A)		Interrupting rating Standard (80 %) rated		
	Hold	Trip	D - 18 kA	G - 35 kA	J ⁽¹⁾ - 65 kA
150	750	1500	NJDL36150	NJGL36150	NJJL36150
175	875	1750	NJDL36175	NJGL36175	NJJL36175
200	1000	2000	NJDL36200	NJGL36200	NJJL36200
225	1125	2250	NJDL36225	NJGL36225	NJJL36225
250	1250	2500	NJDL36250	NJGL36250	NJJL36250

⁽¹⁾ UL Listed/CSA Certified as current limiting circuit breakers.