

Product datasheet

Specifications

16A 30mA Type B Single Module RCBO



DOM16B6R30

⚠ Discontinued on: 31 Mar 2022

⚠ Discontinued

Main

Range of product	Domae
Product or component type	Residual current breaker with overcurrent protection (RCBO)
Poles description	1P
Device location in system	Outgoer

Complementary

[In] rated current	16 A
Network type	AC
[Ue] rated operational voltage	230...240 V AC
Curve code	B
Breaking capacity	6 kA
Connections - terminals	tunnel type terminals

Environment

Standards	BS EN 61009
-----------	-------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
SCIP Number	A7b24ae6-2312-4e67-b7c9-56fce3e8c723
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins