


# Product datasheet

Specifications



servo motor BCH16, Lexium 16D,  
130mm, shaft 22mm, 1.0kW, High  
inertia, 2000rpm, 23bit, brake

BCH16HM10232F6C2

## Main

Range compatibility	Easy Lexium 16
Device short name	BCH16
Product or component type	Servo motor

## Complementary

Maximum mechanical speed	3000 rpm
[Us] rated supply voltage	220 V
Network number of phases	3 phases
Continuous stall current	5.2 A
Continuous stall torque	4.77 N.m for LXM16D at 10.13 A, 220 V, single phase
Continuous power	1000 W
Peak stall torque	14.31 N.m for LXM16D at 10.13 A, 220 V, single phase
Nominal output power	1000 W for LXM16D at 10.13 A, 220 V, single phase
Nominal torque	4.77 N.m for LXM16D at 10.13 A, 220 V, single phase
Nominal speed	2000 rpm for LXM16D at 10.13 A, 220 V, single phase
Maximum current Irms	21.9 A for LXM16D at 1.0 kW, 220 V
Maximum permanent current	15.6 A
Product compatibility	LXM16D motion servo motors motor at 1 kW, 220 V, single phase
Shaft end	Parallel key
Second shaft	Without second shaft end
Shaft diameter	22 mm
Shaft length	35 mm
Key width	8 mm
Feedback type	23 bit high resolution encoder
Holding brake	With
Holding torque	15.0 N.m built-in
Mounting support	Asian standard flange
Motor flange size	130 mm
Electrical connection	Connector MIL
Torque constant	0.92 N.m/A at 20 °C
Back emf constant	60.8 V/krpm at 20 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>Rotor inertia</b>	11.58 kg.cm <sup>2</sup>
<b>Stator resistance</b>	1.2 Ohm at 20 °C
<b>Stator inductance</b>	9.5 mH at 20 °C
<b>Stator electrical time constant</b>	7.92 ms at 20 °C
<b>Maximum radial force Fr</b>	578.2 N at 2000 rpm
<b>Maximum axial force Fa</b>	211.68 N
<b>Brake pull-in power</b>	19.6 W
<b>Type of cooling</b>	Natural convection
<b>Length</b>	186.9 mm
<b>Centring collar diameter</b>	110 mm
<b>Centring collar depth</b>	6 mm
<b>Number of mounting holes</b>	4
<b>Mounting holes diameter</b>	9 mm
<b>Circle diameter of the mounting holes</b>	145 mm
<b>Distance shaft shoulder-flange</b>	50 mm
<b>Width</b>	130 mm
<b>Height</b>	183.4 mm
<b>Depth</b>	186.9 mm
<b>Net weight</b>	7.3 kg

## Environment

<b>IP degree of protection</b>	IP65 IM B5, IM V1 IP65 IM V3
<b>Ambient air temperature for operation</b>	0...40 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	27.5 cm
<b>Package 1 Width</b>	18 cm
<b>Package 1 Length</b>	36 cm
<b>Package 1 Weight</b>	8.138 kg

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	8 438 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Carbon footprint of the manufacturing phase [A1 to A3]	124 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	8 312 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.8 kg CO2 eq.

### Use Better



### Materials and Packaging

Packaging made with recycled cardboard	No
Packaging without single use plastic	No

### Use Longer



### Lifetime extension

Repair	No
--------	----

### Use Again



### Repack and remanufacture

End of life manual availability	<a href="#">End of Life Information</a>
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins