



Figure similar

\*\*\*spare part\*\*\* SIMATIC S7-300, connection IM 361 in expansion rack for connection to central rack (IM360), supply voltage 24 V DC, with C-bus

Supply voltage		
Rated value (DC)	Yes	
• 24 V DC		
Input current		
from supply voltage L+, max.	500 mA	
Power loss		
Power loss, typ.	5 W	
Hardware configuration		
Number of interfaces per CPU, max.	3	
Dimensions		
Width	80 mm	
Height	125 mm	
Depth	120 mm	
Weights		
Weight, approx.	505 g	
Classifications		
	<b>Version</b>	<b>Classification</b>
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05
Approvals / Certificates		
General Product Approval		



[Manufacturer Declaration](#)



General Product Approval    EMV    For use in hazardous locations

[Manufacturer Declaration](#)



EM



For use in hazardous locations    Maritime application



[Miscellaneous](#)

[CCC-Ex](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

last modified:

4/7/2025