

Product data sheet

Specifications



ASCO 300 Manual Transfer Switch with Quick Connects

ASCOLVMTSQC300

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type	Switching device
Intended Application	Commercial Industrial Application

Complementary

Current Rating	30...3000 A
Number of Phases	Single phase Three phase
Number of Poles	2P 3P
Rated Voltage	208...600 V AC 50/60 Hz
Neutral Configurations	Solid neutral Switched neutral
Manual or Delayed Transfer Mode	Manual
Communication Network Type	RS485 Ethernet Modbus
Ambient Air Temperature for Operation	23...104 °F (-5...40 °C)
Operating Altitude	> 6561.68 ft (2000 m)
Max Humidity Rating at 40 C	50 %
Service Entrance Rated	Option
Bypass Isolation Functionality	No
Operating Mode	Manual
Provided Equipment	LED
Electrical Connections	Quick connect terminals
Switch Function	3 positions

Environmental

NEMA Degree of Protection	NEMA 3R/4X/12
Standards	UL 1008 IEC 60947-6-1

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Nbr. of units in pkg. 1

Contractual warranty

Warranty (in months) 24



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

Use Longer



Lifetime extension

Repair

No