

Product data sheet

Specifications



shunt trip release SHT - 24..8 V AC,
24..48 V DC - for EZC400

EZ4SHT048ACDC

⚠ Discontinued on: Nov 1, 2020

⚠ Discontinued

Main

Range	EasyPact
Range of product	EZC400
Device short name	SHT
Product or component type	Voltage release
Device application	Control
Voltage release type	Shunt trip release
[Uc] control circuit voltage	24...48 V AC 50/60 Hz 24...48 V DC
Circuit breaker mounting mode	Internal mounting
Range compatibility	EasyPact EasyPact EZC

Complementary

Operating threshold	0.7 Un opening
Control signal type	Impulse Maintained
Impulse duration	>= 20 ms
Supply inrush power	35 W 30 VA
Auxiliary connection terminal	Pre-wired 0...1.5 mm ²

Contractual warranty

Warranty (in months)	18
----------------------	----

List Price displayed is VAT EXCLUSIVE.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant](#)

PVC free

Yes

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins