

Product data sheet

Specifications



ASCO 4000 Bypass Transfer Switch

ASCOLVATB4000

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Automatic transfer switch
Bypass kit

Intended Application Industrial Application

Complementary

Rated Current 30...4000 A

Number of Phases Single phase
Three phase

Number of Poles 2P
3P
4P

Rated Voltage 208...600 V AC 50/60 Hz

Neutral Configurations Solid neutral
Switched neutral

Open or Closed Transfer Mode Open
Closed

Manual or Delayed Transfer Mode Delayed

Transfer Speed < 100 ms

Controller Group 5

Communication Network Type RS485
Ethernet
Modbus

Ambient Air Temperature for Operation 23...104 °F (-5...40 °C)

Operating Altitude > 6561.68 ft (2000 m)

Max Humidity Rating at 40 C 50 %

Service Entrance Rated No

Bypass Isolation Functionality Yes

Operating Mode AUTO

Display Type Monochrome

Signalling Function LED operating state

Switch Application Isolation

Environmental

NEMA Degree of Protection NEMA 3R/4X/12

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Standards	UL 1008 IEC 60947-6-1
------------------	--------------------------

Contractual warranty

Warranty (in months)	24
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

Use Longer



Lifetime extension

Repair

No

Image of product / Alternate images

Alternative

