



SIMATIC ET 200SP BaseCarrier, for 15 mm I/O modules, BU type A0, bridged to the left, pack quantity: 10 units, WxH: 15x 117 mm

General information	
Product type designation	BU type A0
HW functional status	from FS01
Installation type/mounting	
PCB installation	Yes
Hardware configuration	
Formation of potential groups	
• New potential group	No
• Potential group continued from the left	Yes
Slots	
• Number of slots	1; Type A0
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-30 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-30 °C
• vertical installation, max.	50 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Dimensions	
Width	15 mm
Height	117 mm
Depth	32 mm
Weights	
Weight, approx.	5 g
Classifications	

	Version	Classification
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	10	EC001598
ETIM	9	EC001598
ETIM	8	EC001598

Approvals / Certificates

General Product Approval	Environment
--------------------------	-------------

[Manufacturer Declaration](#)



last modified: 9/24/2025