

Product data sheet

Specifications



TeSys F contactor - 4P (4 NO) - AC-1 - <= 440 V 200 A - coil 24 V DC

LC1F1154BD

⚠ Discontinued on: Jul 2, 2025

⚠ Discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	TeSys
Range of Product	TeSys F
Product or Component Type	Contactor
Device short name	LC1F
Contactor application	Resistive load
Utilisation category	AC-1
Poles description	4P
[Ue] rated operational voltage	<= 690 V AC 50/60 Hz <= 460 V DC
[Uc] control circuit voltage	24 V DC
[Ie] rated operational current	200 A (at <104 °F (40 °C)) at <= 440 V AC-1

Complementary

[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	200 A (at 104 °F (40 °C))
Rated breaking capacity	920 A conforming to IEC 60947-4-1
[Icw] rated short-time withstand current	1100 A 104 °F (40 °C) - 10 s 640 A 104 °F (40 °C) - 30 s 520 A 104 °F (40 °C) - 1 min 400 A 104 °F (40 °C) - 3 min 320 A 104 °F (40 °C) - 10 min
Associated fuse rating	125 aM at <= 440 V 200 A gG at <= 440 V
Average impedance	0.37 mOhm - Ith 200 A 50 Hz
[Ui] rated insulation voltage	1000 V IEC 60947-4-1 1500 V VDE 0110 group C
Power dissipation per pole	15 W AC-1
Overvoltage category	III
power pole contact composition	4 NO
Control circuit voltage limits	Operational 0.85...1.1 Uc 131 °F (55 °C)) Drop-out 0.15...0.2 Uc 131 °F (55 °C))
Mechanical durability	10 Mcycles
Inrush power in W	560 W 68 °F (20 °C))

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Hold-in power consumption in W	4.5 W 68 °F (20 °C)
Maximum operating rate	2400 cyc/h 131 °F (55 °C)
Operating time	30...40 ms closing 30...50 ms opening
Connections - terminals	Power circuit bar 2 20 x 3 mm Power circuit lugs-ring terminals 1 0.1 in² (95 mm²) Power circuit connector 1 0.1 in² (95 mm²) Control circuit screw clamp terminals 1 0.002...0.006 in² (1...4 mm²)flexible without cable end Control circuit screw clamp terminals 2 0.002...0.006 in² (1...4 mm²)flexible without cable end Control circuit screw clamp terminals 1 0.002...0.006 in² (1...4 mm²)flexible with cable end Control circuit screw clamp terminals 2 0.002...0.004 in² (1...2.5 mm²)flexible with cable end Control circuit screw clamp terminals 1 0.002...0.006 in² (1...4 mm²)solid without cable end Control circuit screw clamp terminals 2 0.002...0.006 in² (1...4 mm²)solid without cable end Power circuit bolted connection
Tightening torque	Power circuit 88.5 lbf.in (10 N.m) Control circuit 10.6 lbf.in (1.2 N.m)
Mounting Support	Plate
Heat dissipation	4.5 W
Standards	IEC 60947-4-1 EN 60947-4-1 IEC 60947-1 JIS C8201-4-1 EN 60947-1
Product Certifications	CCC ABS RINA BV UL LROS (Lloyds register of shipping) CB RMRoS DNV UKCA
Compatibility code	LC1F
Control circuit type	DC standard

Environment

IP degree of protection	IP2X front face with shrouds IEC 60529 IP2X front face with shrouds VDE 0106
Protective treatment	TH
Ambient Air Temperature for Operation	-40...140 °F (-40...60 °C)
Ambient Air Temperature for Storage	-76...176 °F (-60...80 °C)
Permissible ambient air temperature around the device	140...158 °F (60...70 °C) at Uc
Height	6.4 in (162 mm)
Width	7.9 in (200.5 mm)
Depth	6.7 in (171 mm)
Operating altitude	9842.52 ft (3000 m) without derating
Net Weight	8.44 lb(US) (3.83 kg)

Ordering and shipping details

Category	US10I1222331
Discount Schedule	0I12
GTIN	3389118093331
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	8.7 in (22.0 cm)
Package 1 Width	8.5 in (21.5 cm)
Package 1 Length	10.4 in (26.5 cm)
Package weight(Lbs)	10.69 lb(US) (4.85 kg)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	787 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint of the manufacturing phase [A1 to A3]	78 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.8 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.4 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	700 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	7 kg CO2 eq.

Use Better



Materials and Substances

EU RoHS Directive	Compliant with Exemptions
SCIP Number	B2d4179a-eb65-40a3-a1ef-d9a33060486f
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	91
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.