

EXN45T3HCU

Low voltage transformer, DOE 2016, dry type,
3 phase, 45kVA, 480V pri, 208Y/120V sec, Cu,
150C rise, Type 2



Main

Range of Product	Square D
Product or Component Type	DOE 2016 energy efficient transformer
Device short name	DOE 2016
Transformer type	Energy efficient
Device Application	Low voltage electrical distribution

Complementary

Box number	19M
Phase	3 phase
Rated operational power in VA	45 kVA
Network Frequency	60 Hz
Type of cooling	Natural convection
Primary Voltage	480 V delta
Number of tap-offs	2 2.5 % FCAN 4 2.5 % FCBN
Primary operational current	54.13 A 124.91 A 45 kVA
Secondary voltage	208Y/120 V
Coil Material	Copper
Basic IMP level (BIL)	10 kV
Temperature Rise	150 °C 220 °C insulated
DOE Efficiency	98.51 % at 35 % load factor , 167 °F (75.0 °C)
Sound Level	6 DB NEMA ST-20 39 dB
%IZ	3.44 %
%IX	1.68 %
X/R Ratio	0.59
Inrush current	709 A
Let Through Current	4.03 kA
Transformer Losses	99 no load (core loss) 1384 load loss (coil loss)
Transformer BTU/HR	469 16.6 % 633 25 % 1518 50 % 2994 75 % 5060 100 %
Height	29.33 in (745 mm)
Depth	25.94 in (659 mm)
Width	25.51 in (648 mm)
Net Weight	398.99 lb(US) (180.98 kg)

Mounting support	Floor Floor, with 7400FMB Ceiling, with 7400CMB18M19M20M Wall, with 7400WMB18M19M20M
Degree of protection	UL type 2 UL type 3R, with 7400WS18M19M20M
Electrical connection	2 Hole Nema Pad secondary 0.44 in (11.1 mm) 4 Hole Nema Pad sec - XO 0.44 in (11.1 mm) 2 Hole Nema Pad primary 0.44 in (11.1 mm)
Number of mounting holes	4 Ø: 0.51 in (13 mm)

Environment

Ambient Air Temperature for Operation	104 °F (40 °C)
Average ambient air temperature for operation	30 °C
Standards	UL 1561 CSA C22.2 No 47 NEMA ST-20

Ordering and shipping details

Category	16256-3PH EXN/2016 15-150KVA LVGP XFMR
Discount Schedule	PE2X
GTIN	785901413233
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	35.40 in (89.916 cm)
Package 1 Width	32.00 in (81.28 cm)
Package 1 Length	31.00 in (78.74 cm)
Package 1 Weight	423.00 lb(US) (191.87 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes