

Product data sheet

Specifications



Disconnect switch, Tesys VLS, fuse holder, for 3 pole disconnect switch, for up to 32A, 10.3 by 38 mm fuse

VLSFH1

⚠ Discontinued on: Jul 31, 2024

⚠ Discontinued

Main

Range	TeSys
Product name	TeSys VARIO LS
Device short name	VLSFH
Fuse size	10.3 x 38 mm
Product or Component Type	Fuse holder
Poles description	3P
Network type	AC

Complementary

Network Frequency	50/60 Hz
Mounting Support	DIN rail
[Ui] rated insulation voltage	690 V AC 50/60 Hz
[Ith] conventional free air thermal current	32 A 131 °F (55 °C)
Connections - terminals	Power circuit screw clamp terminals 0.02 in ² (10 mm ²) solid Power circuit screw clamp terminals 0.02 in ² (16 mm ²) flexible without cable end
Tightening torque	Power circuit 15.9...17.7 lbf.in (1.8...2 N.m) screw clamp terminals
Height	3.0 in (75.2 mm)
Width	2.07 in (52.5 mm)
Depth	3.2 in (80.1 mm)
Net Weight	0.291 lb(US) (0.132 kg)

Environment

Standards	IEC 60947-3
IP degree of protection	IP20 IEC 60529
Ambient air temperature for operation	-13...131 °F (-25...55 °C)

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No