



Figure similar

MAINS CHOKE; UN(V):690; F(HZ):60; I_{EFF}(A):360; LN(MH):0,27; EN 61558-2-20; TA/ISOKL:45 /H

General technical data		
product designation		Netzdrossel
phase number		3
type of voltage		AC
operating voltage rated value	V	690, 690
operating frequency rated value	Hz	50 ... 60
•		
— operational current at AC rated value	A	324
— current at AC maximum	A	360
inductivity rated value	H	0.00027
relative inductive drop in voltage for rated value of the current, voltage and frequency	%	9.2
power loss [W] of the coil	W	975
power loss [W] of the iron core	W	579
Mechanical data		
type of electrical connection for main current circuit		flat connector
width	m	0.41
height	m	0.385
depth	m	0.229
Ambient conditions		
thermal class according to IEC 60085		H
ambient temperature rated value	°C	45
protection class IP		IP00
Certificates/ approvals		
General Product Approval	other	Environment



[Confirmation](#)



[Environmental Confirmations](#)

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
 Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
 Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>
 Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4EU3951-0BA10-0A>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=4EU3951-0BA10-0A>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4EU3951-0BA10-0A>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=4EU3951-0BA10-0A&lang=en

last modified:

8/8/2025 