

# Product data sheet

Specifications

SQUARE D



## DRUM SWITCH 600VAC 7.5HP B +OPTIONS

2601BG1F

! Discontinued

### Main

Device short name B

### Complementary

Cam switch function Reversing switch

Depth 4.86 in (123.44 mm)

Device Application Manual reversing control

Device mounting Flush

Electrical Connection Screw clamp terminal

Enclosure type Standard environment enclosure indoor

Height 6.62 in (168.15 mm)

Maximum Horse Power Rating  
1.5 hp 115 V AC, 1 phase  
5 hp 200/230 V AC, 3 phase  
3 hp 230 V AC, 1 phase  
5 hp 460/575 V AC, 3 phase  
7.5 hp 460/575 V AC, 1 phase

Number of poles 3

Permissible voltage  
600 V AC  
250 V DC

Type of operator Fluted knob

Width 3.26 in (82.80 mm)

### Environment

NEMA Degree of Protection NEMA 1

Product Certifications  
UL Listed  
CSA

### Ordering and shipping details

Category 21116-2601

Discount Schedule CP1

Returnability No

Country of origin MX

### Packing Units

Unit Type of Package 1 PCE

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

<b>Nbr. of units in pkg.</b>	1
<b>Package weight(Lbs)</b>	21.60 oz (612.35 g)

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No