

# Product datasheet

Specifications



## TeSys Deca thermal overload relays - 1...1.6 A - class 20

LR3D06L6

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

### Main

|                                     |                                                                                                                                     |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Range                               | TeSys                                                                                                                               |
| Product name                        | TeSys LRD<br>TeSys Deca                                                                                                             |
| Product or component type           | Non differential thermal overload relay                                                                                             |
| Device short name                   | LR3D                                                                                                                                |
| Relay application                   | Motor protection                                                                                                                    |
| Product compatibility               | LC1D25<br>LC1D18<br>LC1D32<br>LC1D09<br>LC1D38<br>LC1D12                                                                            |
| Network type                        | AC<br>DC                                                                                                                            |
| Thermal overload class              | Class 20 conforming to IEC 60947-4-1                                                                                                |
| Thermal protection adjustment range | 1...1.6 A                                                                                                                           |
| [Ui] rated insulation voltage       | Power circuit: 600 V conforming to CSA<br>Power circuit: 600 V conforming to UL<br>Power circuit: 690 V conforming to IEC 60947-4-1 |

### Complementary

|                                                          |                                                                                           |
|----------------------------------------------------------|-------------------------------------------------------------------------------------------|
| Network frequency                                        | 0...400 Hz                                                                                |
| Mounting support                                         | Plate, with specific accessories<br>Rail, with specific accessories<br>Under contactor    |
| Tripping threshold                                       | 1.14 +/- 0.06 I <sub>r</sub> conforming to IEC 60947-4-1                                  |
| Auxiliary contact composition                            | 1 NO + 1 NC                                                                               |
| [I <sub>th</sub> ] conventional free air thermal current | 5 A for signalling circuit                                                                |
| Permissible current                                      | 3 A at 120 V AC-15 for signalling circuit<br>0.22 A at 125 V DC-13 for signalling circuit |
| [U <sub>e</sub> ] rated operational voltage              | 690 V AC 0...400 Hz for power circuit conforming to IEC 60947-4-1                         |
| Associated fuse rating                                   | 4 A gG for signalling circuit<br>4 A BS for signalling circuit                            |
| [U <sub>imp</sub> ] rated impulse withstand voltage      | 6 kV                                                                                      |
| Phase failure sensitivity                                | Tripping current 130 % of I <sub>r</sub> on two phase, the last one at 0                  |
| Control type                                             | Red push-button: stop<br>Blue push-button: reset                                          |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                          |                                                                                                                                                                                                                                                                                                                  |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Temperature compensation | -20...60 °C                                                                                                                                                                                                                                                                                                      |
| Connections - terminals  | Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm² flexible without cable end<br>Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm² flexible with cable end<br>Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm² solid without cable end<br>Power circuit: lugs-ring terminals |
| Tightening torque        | Control circuit: 1.7 N.m - on screw clamp terminals<br>Power circuit: 2.3 N.m - on lugs-ring terminals M4                                                                                                                                                                                                        |
| Height                   | 66 mm                                                                                                                                                                                                                                                                                                            |
| Width                    | 45 mm                                                                                                                                                                                                                                                                                                            |
| Depth                    | 76 mm                                                                                                                                                                                                                                                                                                            |
| Net weight               | 0.144 kg                                                                                                                                                                                                                                                                                                         |

## Environment

|                                       |                                                                                                                                      |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Climatic withstand                    | conforming to IACS E10                                                                                                               |
| IP degree of protection               | IP20 conforming to IEC 60529                                                                                                         |
| Ambient air temperature for operation | -20...60 °C without derating conforming to IEC 60947-4-1                                                                             |
| Ambient air temperature for storage   | -60...70 °C                                                                                                                          |
| Mechanical robustness                 | Shocks: 15 Gn for 11 ms conforming to IEC 60068-2-7<br>Vibrations: 3 GN conforming to IEC 60068-2-6                                  |
| Dielectric strength                   | 1.89 kV at 50 Hz conforming to IEC 60947-1                                                                                           |
| Standards                             | EN/IEC 60947-4-1<br>EN/IEC 60947-5-1<br>UL 60947-4-1<br>UL 60947-5-1<br>CSA C22.2 No 60947-4-1<br>CSA C22.2 No 60947-5-1<br>EN 50495 |
| Product certifications                | IEC<br>UL<br>CSA<br>EAC<br>ABS<br>ATEX INERIS                                                                                        |

## Packing Units

|                              |        |
|------------------------------|--------|
| Unit Type of Package 1       | PCE    |
| Number of Units in Package 1 | 1      |
| Package 1 Height             | 8.3 cm |
| Package 1 Width              | 7.2 cm |
| Package 1 Length             | 4.5 cm |
| Package 1 Weight             | 144 g  |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

EU RoHS Directive

[Compliant](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins