

Product data sheet

Specifications

SQUARE D



Meter mains, QO, CSED, ringless socket, 400A, surface mount, maximum 12 spaces, Class 320 with lever bypass

QU12L400CL150

Discontinued

Discontinued on: Oct 8, 2021

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product or Component Type	Meter Mains
Range of Product	QO
Includes	Fifth jaw

Complementary

Line Rated Current	400 A
Short-circuit current	25 kA
Network number of phases	1
Meter socket type	Ringless
Mounting	Surface Semi flush with field installed flange kit
Number of spaces	12
Number of circuits	0
Number of Tandem Breakers	0
Hub type	A-L
Electrical connection	Lugs, service ground Studs, line side
Wire Size	AWG 4...250 kcmil copper or aluminium)service ground
Disconnect	Service disconnect (factory installed) Service disconnect (ordered separately)
Main Breaker Rating	150 A
Service feed location	UG
Bypass type	Class 320 lever bypass
Height	43.00 in (1092.20 mm)
Width	28.25 in (717.55 mm)
Depth	7.87 in (199.90 mm)

Environment

Product certifications	UL E-6294
------------------------	-----------

Ordering and shipping details

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Category	US1DE3A00022
Discount Schedule	DE3A
GTIN	785901861386
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	9.9 in (25.1 cm)
Package 1 Width	29.3 in (74.4 cm)
Package 1 Length	43.3 in (110 cm)
Package weight(Lbs)	111.999 lb(US) (50.802 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer

 Lifetime extension	
Repair	No

Use Again

 Repack and remanufacture	
Circularity Profile	No need of specific recycling operations