

Product datasheet

Specifications



auxiliary early-break contact - TeSys GS - 1 OC - 630...1250 A

GS1AM3

⚠ Discontinued on: 5 Aug 2021

⚠ Discontinued

Main

Range of product	TeSys GS 630...1250
Device short name	auxiliary early break and signalling contact
Product or component type	Auxiliary contact
Product compatibility	GS 630...1250
Contacts type and composition	3 C/O
[Ie] rated operational current	12 A at 24 V DC-13 2 A at 440 V AC-15 2 A at 48 V DC-13 3 A at 400/415 V AC-15 4 A at 230 V AC-15 5 A at 127 V AC-15 0.4 A at 220 V DC-13 0.6 A at 110 V DC-13

Complementary

Fuse type	DIN NFC BS
-----------	------------------

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant](#)

Use Longer



Lifetime extension

Repair

No