



Catalog No. TH4363

Description: 100A 3P HD N1 600V FUSIBLE SWITCH

UPC No 783164604801

Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty

- Designed for commercial and industrial applications where safety, high performance and continuity of service are essential.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type HD.
- Fusible and non-fusible switches available (consult BuyLog for interrupt ratings).
- Quick-make, quick-break mechanism.
- 60/75°C conductor rating.
- Full cover interlocks.



Representative Image

Descriptors

Category	Heavy Duty
GO Schedule	S1

Specifications

Amperage	100 A
Poles	3
Wires	3
Fusing	Fusible
Enclosure	NEMA 1 (Indoor)
Options	None
Wire Range (Cu/Al)	10-1/0
480 Vac, NEC Std, 1-ph	10 hp
480 Vac, NEC Std, 3-ph	25 hp
480 Vac, Time Delay, 1-ph	30 hp
480 Vac, Time Delay, 3-ph	60 hp
600 Vac, NEC Std, 1-ph	15 hp
600 Vac, NEC Std, 3-ph	30 hp
600 Vac, Time Delay, 1-ph	40 hp
600 Vac, Time Delay, 3-ph	75 hp
125 Vdc	3 hp
250 Vdc	20 hp

Classifications

cUL Listed	Yes
UL Listed	Yes



Dimensions

Height	22,3 in
Depth	4,8 in
Width	9,3 in
Weight	18 lb