





Magnetic coil for contactor Magnetic coil for contactor 30...250 V DC, screw terminal,

product brand name	SIRIUS
product designation	Magnet coil
General technical data	
Substance Prohibitance (day/month/year)	03/01/2017
Net Weight	0.109 kg
type of voltage of the control supply voltage	AC
control supply voltage 1 at AC	
• at 50 Hz rated value	24 V
operating range factor control supply voltage rated value of magnet coil at AC	
• at 50 Hz	0.8 ... 1.1
apparent pick-up power of magnet coil at AC	
• at 50 Hz	104 VA
• at 60 Hz	120 VA
inductive power factor with closing power of the coil	
• at 50 Hz	0.78
• at 60 Hz	0.7
apparent holding power of magnet coil at AC	
• at 50 Hz	9.7 VA
• at 60 Hz	10.1 VA
inductive power factor with the holding power of the coil	
• at 50 Hz	0.42
• at 60 Hz	0.42

Approvals Certificates

Environment	General Product Approval	EMV	other
Environmental Confirmations		 EG-Konf.	 RCM
			Confirmation 

Further information

- Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT5934-5AB01>
- Cax online generator
<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT5934-5AB01>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3RT5934-5AB01>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT5934-5AB01&lang=en

last modified: 4/3/2025 