








Contactora AC 48 V 50 HZ AC3 30 kW 400 V 3-pole, size S3 screw terminal

| | |
|--|------------------------------|
| product brand name | SIRIUS |
| product designation | Power contactor |
| product type designation | 3RT5 |
| General technical data | |
| size of contactor | S3 |
| product extension auxiliary switch | Yes |
| power loss [W] for rated value of the current | |
| • at AC in hot operating state per pole | 4.6 W |
| • without load current share typical | 5.46 W |
| type of calculation of power loss current-dependent | quadratic |
| insulation voltage rated value | 1 000 V |
| degree of pollution | 3 |
| surge voltage resistance rated value | 6 kV |
| maximum permissible voltage for protective separation between coil and main contacts according to EN 60947-1 | 690 V |
| shock resistance at rectangular impulse | |
| • at AC | 6.8 g / 5 ms, 4 g / 10 ms |
| shock resistance with sine pulse | |
| • at AC | 10.6 g / 5 ms, 6.2 g / 10 ms |
| mechanical service life (operating cycles) | |
| • of contactor typical | 10 000 000 |
| • of the contactor with added auxiliary switch block typical | 10 000 000 |
| Substance Prohibition (day/month/year) | 03/01/2017 |
| Net Weight | 1.8 kg |
| Ambient conditions | |
| installation altitude at height above sea level maximum | 2 000 m |
| ambient temperature | |
| • during operation | -25 ... +60 °C |
| • during storage | -55 ... +80 °C |
| Main circuit | |
| number of poles for main current circuit | 3 |
| number of NO contacts for main contacts | 3 |
| number of NC contacts for main contacts | 0 |
| operating voltage | |
| • at AC-3 rated value maximum | 1 000 V |
| • at AC-3e rated value maximum | 1 000 V |
| operational current | |
| • at AC-1 up to 690 V | |
| — at ambient temperature 40 °C rated value | 100 A |


| | |
|--|---|
| <ul style="list-style-type: none"> — at ambient temperature 60 °C rated value | 90 A |
| <ul style="list-style-type: none"> ● at AC-3 <ul style="list-style-type: none"> — at 400 V rated value — at 690 V rated value | 65 A 47 A |
| <ul style="list-style-type: none"> ● at AC-3e <ul style="list-style-type: none"> — at 400 V rated value — at 690 V rated value — at 1000 V rated value | 65 A 47 A 25 A |
| connectable conductor cross-section in main circuit at AC-1 | |
| <ul style="list-style-type: none"> ● at 60 °C minimum permissible ● at 40 °C minimum permissible | 35 mm ² 35 mm ² |
| operational current for approx. 200000 operating cycles at AC-4 | |
| <ul style="list-style-type: none"> ● at 400 V rated value ● at 690 V rated value | 28 A 20 A |
| operating power | |
| <ul style="list-style-type: none"> ● at AC-1 <ul style="list-style-type: none"> — at 230 V at 60 °C rated value — at 400 V at 60 °C rated value — at 690 V at 60 °C rated value ● at AC-3 <ul style="list-style-type: none"> — at 230 V rated value — at 400 V rated value — at 500 V rated value — at 690 V rated value ● at AC-3e <ul style="list-style-type: none"> — at 230 V rated value — at 400 V rated value — at 500 V rated value — at 690 V rated value — at 1000 V rated value | 34 kW 59 kW 102 kW 18.5 kW 30 kW 37 kW 45 kW 18.5 kW 30 kW 37 kW 45 kW 30 kW |
| operating power for approx. 200000 operating cycles at AC-4 | |
| <ul style="list-style-type: none"> ● at 400 V rated value ● at 690 V rated value | 15.1 kW 18.6 kW |
| no-load switching frequency | |
| <ul style="list-style-type: none"> ● at AC | 5 000 1/h |
| operating frequency | |
| <ul style="list-style-type: none"> ● at AC-1 maximum ● at AC-3 maximum ● at AC-3e maximum ● at AC-4 maximum | 1 000 1/h 1 000 1/h 1 000 1/h 300 1/h |
| Control circuit/ Control | |
| type of voltage of the control supply voltage | AC |
| control supply voltage at AC | |
| <ul style="list-style-type: none"> ● at 50 Hz rated value | 48 V |
| operating range factor control supply voltage rated value of magnet coil at AC | |
| <ul style="list-style-type: none"> ● at 50 Hz | 0.8 ... 1.1 |
| apparent pick-up power of magnet coil at AC | |
| <ul style="list-style-type: none"> ● at 50 Hz | 218 VA |
| inductive power factor with closing power of the coil | |
| <ul style="list-style-type: none"> ● at 50 Hz | 0.61 |
| apparent holding power of magnet coil at AC | |
| <ul style="list-style-type: none"> ● at 50 Hz | 21 VA |
| inductive power factor with the holding power of the coil | |
| <ul style="list-style-type: none"> ● at 50 Hz | 0.26 |
| Auxiliary circuit | |
| number of NC contacts for auxiliary contacts instantaneous | 0 |

| | | | | |
|--|--|---|---|---|
| contact | | | | |
| number of NO contacts for auxiliary contacts instantaneous contact | 0 | | | |
| operational current at AC-12 maximum | 10 A | | | |
| operational current at AC-15 | | | | |
| • at 230 V rated value | 6 A | | | |
| • at 400 V rated value | 3 A | | | |
| operational current at DC-12 | | | | |
| • at 110 V rated value | 3 A | | | |
| • at 220 V rated value | 1 A | | | |
| operational current at DC-13 | | | | |
| • at 24 V rated value | 6 A | | | |
| • at 110 V rated value | 1 A | | | |
| • at 220 V rated value | 0.3 A | | | |
| contact reliability of auxiliary contacts | 1 faulty switching per 100 million (17 V, 1 mA) | | | |
| UL/CSA ratings | | | | |
| yielded mechanical performance [hp] for 3-phase AC motor at 460/480 V rated value | 50 hp | | | |
| Short-circuit protection | | | | |
| design of the fuse link | | | | |
| • for short-circuit protection of the main circuit | | | | |
| — with type of coordination 1 required | fuse gL/gG: 250 A | | | |
| — with type of coordination 2 required | fuse gL/gG: 125 A | | | |
| • for short-circuit protection of the auxiliary switch required | fuse gL/gG: 10 A | | | |
| Installation/ mounting/ dimensions | | | | |
| mounting position | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface | | | |
| fastening method side-by-side mounting | Yes | | | |
| fastening method | screw and snap-on mounting onto 35 mm and 75 mm DIN rail | | | |
| height | 146 mm | | | |
| width | 70 mm | | | |
| depth | 139 mm | | | |
| Connections/ Terminals | | | | |
| type of electrical connection | | | | |
| • for main current circuit | screw-type terminals | | | |
| • for auxiliary and control circuit | screw-type terminals | | | |
| type of connectable conductor cross-sections for main contacts | | | | |
| • solid or stranded | 2x (2.5 ... 16 mm ²) | | | |
| • finely stranded with core end processing | 2x (2.5 ... 35 mm ²) | | | |
| • finely stranded without core end processing | 2x (10 ... 35 mm ²) | | | |
| type of connectable conductor cross-sections | | | | |
| • for auxiliary contacts | | | | |
| — finely stranded with core end processing | 2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²) | | | |
| • for AWG cables for auxiliary contacts | 2x (20 ... 16), 2x (18 ... 14), 1x 12 | | | |
| Safety related data | | | | |
| product function mirror contact according to IEC 60947-4-1 | Yes | | | |
| Electrical Safety | | | | |
| protection class IP on the front according to IEC 60529 | IP20 | | | |
| touch protection on the front according to IEC 60529 | finger-safe, for vertical contact from the front | | | |
| Approvals Certificates | | | | |
| General Product Approval | EMV | | | |
|  Confirmation |  |  |  |  |
| Maritime application | other | Environment | | |



Further information

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/products?pnid=16027&lc=en-CN>





last modified:

4/4/2026 