

Product data sheet

Specifications



Control unit MicroLogic 7.0H, MasterPact NT drawout, LSIV protections

47303

Main

Range	MasterPact
Range of product	MasterPact NT
Product or component type	Control unit
Trip unit name	MicroLogic 7.0 H
Trip unit technology	Electronic
Range compatibility	Masterpact NT06...16
Device application	Distribution
Number of poles	4P 3P
Protected poles description	4t 3t 3t + N/2
Trip unit protection functions	Selective + earth-leakage protection
Protection type	for overload protection (long time) for short time short-circuit protection for instantaneous short-circuit protection for earth-leakage protection
Trip unit rating	630 A at 50 °C 800 A at 50 °C 1000 A at 50 °C 1250 A at 50 °C 1600 A at 50 °C
Network type	AC
Network frequency	50/60 Hz
Circuit breaker mounting mode	Drawout

Complementary

Long-time pick-up adjustment type I_r (thermal protection)	Adjustable 9 settings
[I_r] long-time protection pick-up adjustment range	0.4...1 x I_n
Long-time protection delay adjustment type t_r	Adjustable 9 settings
[t_r] long-time protection delay adjustment range	0.7...16.6 s at 7.2 x I_r 0.7...24 s at 6 x I_r 12.5...600 s at 1.5 x I_r
Thermal memory	20 mn
Short-time protection pick-up adjustment type I_{sd}	Adjustable 9 settings
[I_{sd}] Short-time protection pick-up adjustment range	1.5...10 x I_r
Short-time protection delay adjustment type t_{sd}	Adjustable

List Price displayed is VAT EXCLUSIVE.

[tsd] Short-time protection delay adjustment range	0...0.4 s I ² t=off 0.1...0.4 s I ² t=on
Instantaneous protection pick-up adjustment type Ii	Adjustable 9 settings
[Ii] instantaneous protection pick-up adjustment range	Off 2...15 x I _n
Earth-leakage protection	Integrated
Earth-leakage protection sensitivity adjustment type IΔn	Adjustable 9 settings
[IΔn] earth-leakage protection sensitivity adjustment range	0.5...30 A
Earth-leakage sensitivity	10 A for class A 30 A for class AC
Earth-leakage protection time delay adjustment type Δt	Adjustable 5 settings
[Δt] Earth-leakage protection time delay adjustment range	60...800 ms
Zone selective interlocking ZSI	With
Local signalling	3 LEDs (red) for electrical fault 1 LED (red) for internal error
Display type	Digital display
Type of measurement	Harmonics meter Power meter
Communication of data	Measurement readout Protection and alarm settings Maintenance indicators

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	6.0 cm
Package 1 Length	20.0 cm
Package 1 Weight	2.112 kg

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	146 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	128 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.3 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	12 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	5 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards
SCIP Number	6ac3934d-9e20-40a3-edef-08cec90e29e2
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds
PVC free	No

Use Longer




Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	3
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	Nej
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

