

# Product datasheet

Specifications



## contactor TeSys Deca - 4 poles - AC-1 440V 60 A - coil 110 V AC

LC1D400046F7

⚠ Discontinued on: 6 July 2020

⚠ Discontinued

### Main

Range of product	TeSys Deca
Product or component type	Contacteur
Device short name	LC1D
Contacteur application	Resistive load
Utilisation category	AC-1
Poles description	4P
[Ue] rated operational voltage	Power circuit: $\leq 690$ V AC 25...400 Hz
[Ie] rated operational current	60 A (at $\leq 60$ °C) AC AC-1 for power circuit
[Uc] control circuit voltage	110 V AC 50/60 Hz

### Complementary

Compatibility code	LC1D
Pole contact composition	4 NO
Protective cover	With
[Ith] conventional free air thermal current	10 A (at 60 °C) for control circuit 60 A (at 60 °C) for power circuit
Irms rated making capacity	140 A AC for control circuit conforming to IEC 60947-5-1 800 A at 440 V for power circuit conforming to IEC 60947
Rated breaking capacity	800 A at 440 V for power circuit conforming to IEC 60947
Associated fuse rating	10 A gG for control circuit conforming to IEC 60947-5-1 80 A gG at $\leq 690$ V coordination type 1 for power circuit 80 A gG at $\leq 690$ V coordination type 2 for power circuit
Average impedance	1.5 mOhm - Ith 60 A 50 Hz for power circuit
Power dissipation per pole	5.4 W AC-1
[Ui] rated insulation voltage	Control circuit: 600 V CSA certified Control circuit: 600 V UL certified Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Control circuit: 690 V conforming to IEC 60947-1 Power circuit: 690 V conforming to IEC 60947-1
Overvoltage category	III
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947
Safety reliability level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical durability	6000000 cycles

<b>Control circuit type</b>	AC at 50/60 Hz standard
<b>Coil technology</b>	Without built-in bidirectional peak limiting diode suppressor
<b>Control circuit voltage limits</b>	0.3...0.6 U <sub>c</sub> (60 °C):drop-out AC 50/60 Hz 0.8...1.1 U <sub>c</sub> (60 °C):operational AC 50 Hz 0.85...1.1 U <sub>c</sub> (60 °C):operational AC 60 Hz
<b>Inrush power in VA</b>	140 VA cos phi 0.75 (at 20 °C)
<b>Hold-in power consumption in VA</b>	13 VA 60 Hz cos phi 0.3 (at 20 °C) 15 VA 50 Hz cos phi 0.3 (at 20 °C)
<b>Heat dissipation</b>	4...5 W at 50/60 Hz for control circuit
<b>Operating time</b>	12...26 ms closing 4...19 ms opening
<b>Connections - terminals</b>	Control circuit: ring lugs 1 - external diameter: 8 mm Power circuit: ring lugs 1 - external diameter: 16.5 mm
<b>Auxiliary contacts type</b>	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1
<b>Minimum switching voltage</b>	17 V for control circuit
<b>Minimum switching current</b>	5 mA for control circuit
<b>Insulation resistance</b>	> 10 MOhm for control circuit
<b>Non-overlap time</b>	1.5 ms on de-energisation between NC and NO contacts 1.5 ms on energisation between NC and NO contacts
<b>Mounting support</b>	Plate Rail

## Environment

<b>Standards</b>	CSA C22.2 No 14 IEC 60947-5-1 EN 60947-5-1 IEC 60947-4-1 UL 508 EN 60947-4-1
<b>Product certifications</b>	LROS (Lloyds register of shipping) BV CSA UL CCC DNV GOST GL RINA
<b>IP degree of protection</b>	IP2X conforming to IEC 60529 IP2X conforming to VDE 0106
<b>Protective treatment</b>	TH (pollution degree 3) conforming to IEC 60068
<b>Permissible ambient air temperature around the device</b>	-5...60 °C -40...70 °C at U <sub>c</sub>
<b>Operating altitude</b>	3000 m without derating
<b>Fire resistance</b>	850 °C conforming to IEC 60695-2-1
<b>Flame retardance</b>	V1 conforming to UL 94
<b>Mechanical robustness</b>	Shocks contactor open (8 Gn for 11 ms) Shocks contactor closed (10 Gn for 11 ms) Vibrations contactor opened (2 Gn, 5...300 Hz) Vibrations contactor closed (4 Gn, 5...300 Hz)
<b>Height</b>	127 mm
<b>Width</b>	85 mm
<b>Depth</b>	125 mm

---

Product weight	1.44 kg
----------------	---------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	13.2 cm
------------------	---------

---

Package 1 Width	13.2 cm
-----------------	---------

---

Package 1 Length	9.5 cm
------------------	--------

---

Package 1 Weight	1.33 kg
------------------	---------

## Contractual warranty

---

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins