

# Product datasheet

Specifications



## Acti9 - Auxiliary contact iOF - 1 C/O - AC/DC

A9A26869

⚠ Discontinued on: 1 Jun 2024

⚠ Discontinued

### Main

range of product	Acti9
Product or component type	OC contact
Device short name	iOF
Signal contacts composition	1 C/O
[In] rated current	DC-12 1 A at 130 V, DC DC-12 1.5 A at 60 V, DC DC-12 2 A at 48 V, DC DC-12 6 A at 24 V, DC AC-12 3 A at 415 V, AC 50/60 Hz AC-12 6 A at 240 V, AC 50/60 Hz
9 mm pitches	1
Standards	EN/IEC 60947-5-1
Product certifications	LCIE ASEFA KEMA ASTA

### Complementary

Range compatibility	Acti9 iC60 Acti9 iID double terminals residual current circuit breaker (RCCB)
Mounting mode	Clip-on
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Bottom: YES
Height	86 mm
Width	9 mm
Depth	73 mm
Net weight	32 g
Colour	White
Connections - terminals	Screw clamp terminal1 cable(s) 0.5...2.5 mm <sup>2</sup> - flexible Screw clamp terminal1 cable(s) 1...4 mm <sup>2</sup> - rigid Screw clamp terminal2 cable(s) 2.5 mm <sup>2</sup> - rigid Screw clamp terminal2 cable(s) 1.5 mm <sup>2</sup> - flexible with ferrule
Wire stripping length	10 mm
Tightening torque	1 N.m

### Environment

IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
-------------------------	-------------------------------------

<b>Pollution degree</b>	3 conforming to EN/IEC 60947-5-1
<b>Tropicalisation</b>	2 conforming to EN/IEC 60947-5-1
<b>Relative humidity</b>	95 % at 55 °C
<b>Ambient air temperature for operation</b>	-35...70 °C
<b>Ambient air temperature for storage</b>	-40...85 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	8 cm
<b>Package 1 Width</b>	2 cm
<b>Package 1 Length</b>	10 cm
<b>Package 1 Weight</b>	46 g
<b>Unit Type of Package 2</b>	S03
<b>Number of Units in Package 2</b>	120
<b>Package 2 Height</b>	30 cm
<b>Package 2 Width</b>	30 cm
<b>Package 2 Length</b>	40 cm
<b>Package 2 Weight</b>	6.35 kg
<b>Unit Type of Package 3</b>	P06
<b>Number of Units in Package 3</b>	960
<b>Package 3 Height</b>	75 cm
<b>Package 3 Width</b>	60 cm
<b>Package 3 Length</b>	80 cm
<b>Package 3 Weight</b>	52.66 kg

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	0.4 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Carbon footprint of the manufacturing phase [A1 to A3]	0.4 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.

### Use Better



### Materials and Substances

Halogen-free status	Halogen free plastic parts product
---------------------	------------------------------------

### Use Longer



### Lifetime extension

Repair	No
--------	----

### Use Again



### Repack and remanufacture

End of life manual availability	<a href="#">End of Life Information</a>
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins