

Product datasheet

Specifications



Bistable contactor CR1-F - 3P - AC-1 440V 185 A - coil 440 V

CR1F185R7

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

Main

Range	TeSys
Product name	TeSys F
Product or component type	Magnetic latching contactor
Device short name	CR1F
Device application	Control
Contactor application	Resistive load Motor control
Utilisation category	AC-4 AC-1 AC-3
Poles description	3P
power pole contact composition	3 NO
[Ue] rated operational voltage	1000 V AC 25...200 Hz
[Ie] rated operational current	185 A (at <40 °C) at <= 440 V AC AC-3 275 A (at <40 °C) at <= 440 V AC AC-1 170 A (at <40 °C) at <= 440 V AC AC-4
Motor power kW	100 kW at 1000 V AC 50/60 Hz 110 kW at 690 V AC 50/60 Hz 110 kW at 500...660 V AC 50/60 Hz 100 kW at 440 V AC 50/60 Hz 100 kW at 415 V AC 50/60 Hz 90 kW at 380...400 V AC 50/60 Hz 55 kW at 220...230 V AC 50/60 Hz
motor power HP (UL / CSA)	150 hp at 575...600 V AC 50/60 Hz for 3 phases motors 125 hp at 460...480 V AC 50/60 Hz for 3 phases motors 60 hp at 220...240 V AC 50/60 Hz for 3 phases motors 50 hp at 200...208 V AC 50/60 Hz for 3 phases motors
[Uc] control circuit voltage	440 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	275 A (at 40 °C) for power circuit
Irms rated making capacity	2100 A for power circuit
Rated breaking capacity	1800 A at 220...440 V for power circuit 1600 A at 500 V for power circuit 600 A at 1000 V for power circuit 1200 A at 660/690 V for power circuit

[Icw] rated short-time withstand current	1500 A 40 °C - 1 s 1500 A 40 °C - 5 s 1500 A 40 °C - 10 s 920 A 40 °C - 30 s 740 A 40 °C - 1 min 500 A 40 °C - 3 min 400 A 40 °C - 10 min
Associated fuse rating	200 aM at <= 440 V for power circuit 315 A BS88 at <= 440 V for power circuit 315 A gG at <= 440 V for power circuit
Average impedance	0.36 mOhm - Ith 275 A 50 Hz
[Ui] rated insulation voltage	1000 V conforming to IEC 60158-1 1000 V conforming to IEC 60947-4 1000 V conforming to BS 775 1500 V conforming to VDE 0110 group C
Power dissipation per pole	12 W AC-3 26 W AC-1
Mounting support	Notched AM1-EC rail Panel mounting
Standards	JEM 1038 BS 5424 IEC 60947-4 NF C 63-110 VDE 0660
Product certifications	CSA Veritas UL USSR BV GL LROS (Lloyds register of shipping) RINA ASE
Connections - terminals	Bars 2 cable(s) - busbar cross section: 25 x 3 mm Lugs-ring terminals 1 cable(s) 150 mm ² Connector 1 cable(s) 150 mm ²
Tightening torque	18 N.m
Operating time	35...40 ms latching 50...100 ms unlatching
Mechanical durability	1 Mcycles
Maximum operating rate	120 cyc/h 40 °C

Complementary

Control circuit voltage limits	Latching: 0.85...1.1 Uc Unlatching: 0.85...1.1 Uc
average consumption	1750 VA AC 50...400 Hz latching 11 VA AC 50...400 Hz unlatching 1750 VA DC latching 11 VA DC unlatching

Environment

IP degree of protection	IP20 front face conforming to IEC 60529
Protective treatment	TH
Ambient air temperature for operation	-15...70 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without derating
Height	174 mm

Width	168.5 mm
Depth	181 mm
Net weight	4.65 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No