



SITOP Inrush current limiter

SITOP Inrush current limiter Ballast unit for SITOP Power supplies input: 100-480 V AC, 10 A max output: 100-480 V AC, 10 A max

General information	
Technical Product Detail Page	https://i.siemens.com/1P6EP1967-2AA00
input	
type of the power supply network	1-phase, 2-phase and 3-phase AC
supply voltage at AC	
• minimum rated value	100 V
• maximum rated value	480 V
• initial value	85 V
• full-scale value	575 V
wide range input	Yes
line frequency	50/60 Hz
line frequency	47 ... 63 Hz
current limitation of inrush current at 25 °C maximum	10 A
duration of inrush current limiting at 25 °C	
• typical	120 ms
fuse protection type in the feeder	Circuit breaker max. 10 A
output	
voltage curve at output	according to the supply voltage
number of outputs	1
output voltage	
• at AC rated value	100 - 480 V
• at AC	85 ... 575
output voltage adjustable	No
display version for normal operation	Green LED
output current	
• rated range	0 ... 10 A
bridging of equipment	No
efficiency	
power loss [W]	
• at rated output voltage for rated value of the output current typical	1.5 W
protection and monitoring	
property of the output short-circuit proof	No
design of short-circuit protection	must be ensured by primary miniature circuit breaker
overcurrent overload capability	
• when switching on	Switching frequency max. 1 event per minute
safety	
galvanic isolation between input and output	No
operating resource protection class	Class II

protection class IP	IP20
EMC	
standard	
• for emitted interference	EN 61000-6-3
• for mains harmonics limitation	-
• for interference immunity	EN 61000-6-2
standards, specifications, approvals	
certificate of suitability	
• CE marking	Yes
• UL approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
• EAC approval	Yes
• NEC Class 2	No
type of certification	
• CB-certificate	No
standards, specifications, approvals hazardous environments	
certificate of suitability	
• IECEx	No
• ATEX	No
• ULhazloc approval	No
• FM registration	No
standards, specifications, approvals marine classification	
shipbuilding approval	No
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	No
• French marine classification society (BV)	No
• Det Norske Veritas (DNV)	No
• Lloyds Register of Shipping (LRS)	No
ambient conditions	
ambient temperature	
• during operation	-25 ... +60 °C; with natural convection
• during transport	-40 ... +85 °C
• during storage	-40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
connection method	
type of electrical connection	screw terminal
• at input	L, N: 1 screw terminal each for 0.5 ... 2.5 mm²
• at output	L, N: 1 screw terminal each for 0.5 ... 2.5 mm²
mechanical data	
width × height × depth of the enclosure	22.5 × 80 × 91 mm
installation width × mounting height	22.5 mm × 180 mm
required spacing	
• top	50 mm
• bottom	50 mm
• left	0 mm
• right	0 mm
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
• DIN-rail mounting	Yes
• S7 rail mounting	No
• wall mounting	No
housing can be lined up	Yes
net weight	0.12 kg
further information internet links	
internet link	
• to website: Industry Mall	https://mall.industry.siemens.com
• to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
• to web page: power supplies	https://siemens.com/sitop
• to website: CAX-Download-Manager	https://siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

additional information	
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert . (V4.7)

Classifications			
		Version	Classification
	eClass	14	27-04-07-01
	eClass	12	27-04-07-01
	eClass	9.1	27-04-07-01
	eClass	9	27-04-07-01
	eClass	8	27-04-90-02
	eClass	7.1	27-04-90-02
	eClass	6	27-04-90-02
	ETIM	10	EC002540
	ETIM	9	EC002540
	ETIM	8	EC002540
	ETIM	7	EC002540
	IDEA	4	4130
	UNSPSC	15	39-12-10-04

Approvals Certificates	
General Product Approval	

[Manufacturer Declaration](#)

[Declaration of Conformity](#)



last modified:

5/5/2026