

Product datasheet

Specifications



voltage release Compact MX - 220..240 V AC 50/60Hz

29387

⚠ Discontinued on: 30 Sept 2020

⚠ End-of-service on: 25 Jan 2021

⚠ Discontinued

Main

Range	ComPact
Range of product	NS400...630 DC NR100...250 NSF150...250 NB400...600 NS100...250 DC NS125E NS400...630 NR400...630 NSJ400...600 NS100...250
Device short name	MX
Product or component type	Voltage release
Device application	Control
Voltage release type	Shunt trip release
[Uc] control circuit voltage	208...277 V AC 60 Hz 220...240 V AC 50/60 Hz
Range compatibility	ComPact ComPact NS ComPact Compact NB ComPact Compact NR ComPact Compact NSF ComPact Compact NSJ

Complementary

Operating threshold	0.7...1.1 x Un
Response time	50 ms
Control signal type	Impulse Maintained
Impulse duration	>= 20 ms
Auxiliary connection terminal	Screw terminal 0...1.5 mm ²

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins