

# Product data sheet

Specifications



## Circuit breaker MasterPact MTZ2 40H, 4000A, 4P drawout, without MicroLogic

LV864692

### Main

Range	MasterPacT
Product name	MasterPact MTZ2
Device short name	MTZ2 40 H
Product or Component Type	Circuit breaker
Device Application	Power distribution protection
Poles description	4P
Neutral position	Left
Control unit	Without control unit
Line Rated Current	4000 A 104 °F (40 °C)
Performance type	H
[Ue] rated operational voltage	240...600 V AC 50/60 Hz
Control Type	Push-button
Mounting Mode	Drawout

### Complementary

[Icu] rated ultimate short-circuit breaking capacity	100 kA 240 V AC 50/60 Hz 100 kA 480 V AC 50/60 Hz 85 kA 600 V AC 50/60 Hz
[Icw] rated short-time withstand current	85 kA 1 s IEC 60947-2
Integrated instantaneous protection (DIN in kA peak)	75 kA
Sensor rating	4000 A
[Ui] rated insulation voltage	1000 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	12 kV
Maximum breaking time	30 ms
Maximum closing response time	70 ms
Mounting Support	Rails Base plate
Upside connection	Front Rear
Downside connection	Front Rear
Connection pitch	4.5 in (115 mm)
Mechanical durability	20000 cycles with periodic preventive maintenance IEC 60947-2

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Height</b>	Drawout circuit breaker without chassis: 11.8 in (300 mm) Drawout circuit breaker with chassis: 17.3 in (439 mm)
<b>Width</b>	Drawout circuit breaker without chassis: 19.4 in (493 mm) Drawout circuit breaker with chassis: 21.9 in (556 mm)
<b>Depth</b>	Drawout circuit breaker without chassis: 11.8 in (300 mm) Drawout circuit breaker with chassis: 15.9 in (403 mm)
<b>Standards</b>	UL 489

## Environment

<b>IP degree of protection</b>	IP30
<b>Pollution degree</b>	3 IEC 60947-1
<b>Ambient Air Temperature for Operation</b>	-13...158 °F (-25...70 °C)
<b>Ambient Air Temperature for Storage</b>	-40...185 °F (-40...85 °C)

## Ordering and shipping details

<b>GTIN</b>	3606480818400
-------------	---------------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	5 883 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Carbon footprint of the manufacturing phase [A1 to A3]	707 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	15 kg CO2 eq.
Carbon footprint of the installation phase [A5]	18 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	4 911 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	232 kg CO2 eq.

### Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Compliant with Exemptions
SCIP Number	F31d8a4d-e9cb-4afc-bf2c-5965742ce772
REACH Regulation	<a href="#">REACH Declaration</a>
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
Halogen content performance	Product contains halogen above thresholds
PVC free	Yes
Silicon free	No

### Use Longer



### Lifetime extension

Repair	No
--------	----

### Use Again



### Repack and remanufacture

Circularity Profile	<a href="#">End of Life Information</a>
Take-back	No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

---