


# Product datasheet

Specifications



## coil, EasyPact NW, XF, 220V, AC/DC

ENW15512

### Main

|                           |                                      |
|---------------------------|--------------------------------------|
| Range of product          | EasyPact NW                          |
| Range                     | EasyPact                             |
| Device short name         | XF                                   |
| Product or component type | Closing coil                         |
| Device application        | Control                              |
| Range compatibility       | EasyPact EasyPact NW circuit breaker |
| Voltage release type      | Closing coil                         |

### Complementary

|                              |                                                                                                                                                                                                                                                                            |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Control type                 | Electrically operated                                                                                                                                                                                                                                                      |
| Control signal type          | Maintained                                                                                                                                                                                                                                                                 |
| [Uc] control circuit voltage | 220/250 V AC/DC 50/60 Hz                                                                                                                                                                                                                                                   |
| Threshold tripping voltage   | Remote control: 0.85...1.1 Un closing                                                                                                                                                                                                                                      |
| Supply holding power         | 4.5 VA<br>4.5 W                                                                                                                                                                                                                                                            |
| Supply inrush power          | 200 VA 200 ms<br>200 W 200 ms                                                                                                                                                                                                                                              |
| Response time                | 70 ms at 800 A (EasyPact MVS)<br>70 ms at 100 A (EasyPact MVS)<br>70 ms at 1250 A (EasyPact MVS)<br>70 ms at 1600 A (EasyPact MVS)<br>70 ms at 2000 A (EasyPact MVS)<br>70 ms at 2500 A (EasyPact MVS)<br>70 ms at 3200 A (EasyPact MVS)<br>70 ms at 4000 A (EasyPact MVS) |

### Packing Units

|                              |        |
|------------------------------|--------|
| Unit Type of Package 1       | PCE    |
| Number of Units in Package 1 | 1      |
| Package 1 Height             | 3.5 cm |
| Package 1 Width              | 6 cm   |
| Package 1 Length             | 8.5 cm |
| Package 1 Weight             | 149 g  |
| Unit Type of Package 2       | BB1    |
| Number of Units in Package 2 | 10     |
| Package 2 Height             | 9 cm   |

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                              |          |
|------------------------------|----------|
| Package 2 Width              | 13 cm    |
| Package 2 Length             | 18.5 cm  |
| Package 2 Weight             | 1.557 kg |
| Unit Type of Package 3       | S02      |
| Number of Units in Package 3 | 60       |
| Package 3 Height             | 15 cm    |
| Package 3 Width              | 30 cm    |
| Package 3 Length             | 40 cm    |
| Package 3 Weight             | 9.486 kg |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 330 kg CO2 eq.                                |
| Carbon footprint of the manufacturing phase [A1 to A3] | 1 kg CO2 eq.                                  |
| Carbon footprint of the distribution phase [A4]        | 0.2 kg CO2 eq.                                |
| Carbon footprint of the installation phase [A5]        | 0 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 328 kg CO2 eq.                                |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 0.4 kg CO2 eq.                                |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                        |                                                                                                                                       |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes                                                                                                                                   |
| Packaging without single use plastic   | No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards |
| SCIP Number                            | 3f2d539a-6ab5-46aa-8603-9354f4ae3294                                                                                                  |
| EU RoHS Directive                      | <a href="#">Compliant By Exemption</a>                                                                                                |
| REACH Regulation                       | <a href="#">Reference contains Substances of Very High Concern above the threshold</a>                                                |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                                 |                                         |
|---------------------------------|-----------------------------------------|
| Recyclability potential, in %   | 68                                      |
| End of life manual availability | <a href="#">End of Life Information</a> |
| Take-back                       | No                                      |

Offer Marketing Illustration

Product benefits / Features

### EasyPact NW

**NFC connectivity**

Offers easy monitoring and allows for proactive actions.

**Colour-coded health status bar**

Offers easy monitoring and allows for proactive actions.

**Simpler commissioning**

Achieve quick and simple commissioning through EPC and mobile EPD.



**Innovative front-end retrofit capability**

Enables upgrades in just 5 minutes, eliminating the need for shutdown.

**Detailed event logs**

Facilitates rapid fault diagnosis with easy access to detailed trip event records.

**Compact frame**

Optimizes switchboard footprints with a compact frame size, offering a higher breaking capacity of up to 66 kA.

4

Schneider Electric

17 May 2026