

Article No. : 6SL3310-1GF33-3AA3




Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data		
Input		
Supply frequency	47...63 Hz	
Supply voltage	500 V ±10 %	
Rated input current	343 A	
Max. current	525 A	
Pulse number	6	
Energy recovery capability	No	(2Q)
Output		
Output voltage	500 V	
Rated power (LO) in kW	200 kW	
Rated power (HO) in kW	160 kW	
Rated output current	330 A	
Rated output current (LO)	320 A	
Rated output current (HO)	280 A	
Output current Max	480 A	
Pulse frequency (factory setting)	1.25 kHz	
Basic data		
Power losses ΔP	5.04 kW	
Sound pressure level L _{pA} (1 m)	69 dB	
Conductor cross section, max. (IEC)	4 x 240 mm ²	
Degree of protection	IP20	
Dimensions (H x W x D)	1,533 mm x 326 mm x 545 mm	
Weight approx.	176 kg	
Frame size	GX	
Environmental conditions		
Installation altitude	1,000 m	
Coolant	Air	
Coolant requirement, air	0.36 m³/s	
Ambient temperature	0 °C - +40 °C	

Converter losses to IEC61800-9-2*	
Efficiency class	IE2
Comparison with the reference converter (90% / 100%)	43.1 %



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard IEC61800-9-2) of the relative torque generating current (I) over the relative motor stator frequency (f). The values are valid for the basic version of the converter without options/components.

*calculated values

Special design
Line-side power components
Load-side power components
DC link components
Supplementary system components
6SL30401GA011AA0 - Control Unit Kit CU320-2 PN (PROFINET, EtherNet/IP)