

# Product data sheet

Specifications



## Reversing contactor, TeSys Deca, 3P(3NO), AC-3, <=440V, 18A, 120V AC 50/60Hz coil

LC2D183G7

⚠ Discontinued

### Main

|   |  |
|---|--|
| Range                                       | TeSys  |
| Product name                                | TeSys Deca   |
| Product or Component Type                   | Reversing contactor  |
| Device short name                           | LC2D   |
| Contactor application                       | Motor control<br>Resistive load  |
| Utilisation category                        | AC-3<br>AC-1   |
| Device presentation                         | Preassembled with reversing power busbar   |
| Poles description                           | 3P   |
| power pole contact composition              | 3 NO   |
| [Ue] rated operational voltage              | Power circuit <= 690 V AC 25...400 Hz<br>Power circuit <= 300 V DC   |
| [Ie] rated operational current              | 25 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit<br>18 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit   |
| Motor power kW                              | 4 kW at 220...230 V AC 50 Hz<br>7.5 kW at 380...400 V AC 50 Hz<br>9 kW at 415...440 V AC 50 Hz<br>10 kW at 500 V AC 50 Hz<br>10 kW at 660...690 V AC 50 Hz   |
| Maximum Horse Power Rating                  | 1 hp at 115 V AC 60 Hz for 1 phase motors<br>3 hp at 230/240 V AC 60 Hz for 1 phase motors<br>5 hp at 200/208 V AC 60 Hz for 3 phase motors<br>5 hp at 230/240 V AC 60 Hz for 3 phase motors<br>10 hp at 460/480 V AC 60 Hz for 3 phase motors<br>15 hp at 575/600 V AC 60 Hz for 3 phase motors |
| Control circuit type                        | AC 50/60 Hz  |
| [Uc] control circuit voltage                | 120 V AC 50/60 Hz  |
| Auxiliary contact composition               | 1 NO + 1 NC  |
| [Uimp] rated impulse withstand voltage      | 6 kV IEC 60947   |
| Overvoltage category                        | III  |
| [Ith] conventional free air thermal current | 10 A (at 140 °F (60 °C)) for signalling circuit<br>25 A (at 140 °F (60 °C)) for power circuit  |
| Irms rated making capacity                  | 140 A AC for signalling circuit conforming to IEC 60947-5-1<br>250 A DC for signalling circuit conforming to IEC 60947-5-1<br>300 A at 440 V for power circuit conforming to IEC 60947   |
| Rated breaking capacity                     | 300 A at 440 V for power circuit conforming to IEC 60947   |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

|   |  |
|---|--|
| <b>[Icw] rated short-time withstand current</b> | 40 A 104 °F (40 °C) - 10 min for power circuit<br>84 A 104 °F (40 °C) - 1 min for power circuit<br>145 A 104 °F (40 °C) - 10 s for power circuit<br>240 A 104 °F (40 °C) - 1 s for power circuit<br>100 A - 1 s for signalling circuit<br>120 A - 500 ms for signalling circuit<br>140 A - 100 ms for signalling circuit   |
| <b>Associated fuse rating</b>                   | 10 A gG for signalling circuit conforming to IEC 60947-5-1<br>50 A gG at <= 690 V coordination type 1 for power circuit<br>35 A gG at <= 690 V coordination type 2 for power circuit   |
| <b>Average impedance</b>                        | 2.5 mOhm - lth 25 A 50 Hz for power circuit  |
| <b>[Ui] rated insulation voltage</b>            | Power circuit 690 V IEC 60947-4-1<br>Power circuit 600 V CSA<br>Power circuit 600 V UL<br>Signalling circuit 690 V IEC 60947-1<br>Signalling circuit 600 V CSA<br>Signalling circuit 600 V UL  |
| <b>Electrical durability</b>                    | 1.65 Mcycles 18 A AC-3 <= 440 V<br>1 Mcycles 32 A AC-1 <= 440 V  |
| <b>Power dissipation per pole</b>               | 0.8 W AC-3<br>2.5 W AC-1   |
| <b>Front cover</b>                              | With   |
| <b>Interlocking type</b>                        | Mechanical   |
| <b>Mounting Support</b>                         | Rail<br>Plate  |
| <b>Standards</b>                                | CSA C22.2 No 14<br>EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 508  |
| <b>Product Certifications</b>                   | GOST<br>LROS (Lloyds register of shipping)<br>BV<br>RINA<br>CSA<br>GL<br>DNV<br>UL<br>CCC  |
| <b>Connections - terminals</b>                  | Control circuit spring terminals 1 0.004 in <sup>2</sup> (2.5 mm <sup>2</sup> )flexible without cable end<br>Control circuit spring terminals 2 0.004 in <sup>2</sup> (2.5 mm <sup>2</sup> )flexible without cable end<br>Power circuit spring terminals 1 0.006 in <sup>2</sup> (4 mm <sup>2</sup> )flexible without cable end<br>Power circuit spring terminals 2 0.006 in <sup>2</sup> (4 mm <sup>2</sup> )flexible without cable end |
| <b>Operating time</b>                           | 12...22 ms closing<br>4...19 ms opening  |
| <b>Safety reliability level</b>                 | B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1   |
| <b>Mechanical durability</b>                    | 15 Mcycles   |
| <b>Maximum operating rate</b>                   | 3600 cyc/h 140 °F (60 °C)  |

## Complementary

|                                       |   |
|---------------------------------------|---|
| <b>Coil technology</b>                | Without built-in suppressor module  |
| <b>Control circuit voltage limits</b> | 0.3...0.6 Uc (-40...158 °F (-40...70 °C)):drop-out AC 50/60 Hz<br>0.8...1.1 Uc (-40...140 °F (-40...60 °C)):operational AC 50 Hz<br>0.85...1.1 Uc (-40...140 °F (-40...60 °C)):operational AC 60 Hz<br>1...1.1 Uc (140...158 °F (60...70 °C)):operational AC 50/60 Hz |
| <b>Inrush power in VA</b>             | 70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C))<br>70 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C))  |

|  |   |
|--|---|
| <b>Hold-in power consumption in VA</b> | 7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C))<br>7 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))                |
| <b>Heat dissipation</b>                | 2...3 W 50/60 Hz  |
| <b>Auxiliary contacts type</b>         | Mechanically linked 1 NO + 1 NC IEC 60947-5-1<br>Mirror contact 1 NC IEC 60947-4-1                      |
| <b>Signalling circuit frequency</b>    | 25...400 Hz   |
| <b>Minimum switching current</b>       | 5 mA for signalling circuit   |
| <b>Minimum switching voltage</b>       | 17 V for signalling circuit   |
| <b>Non-overlap time</b>                | 1.5 ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact |
| <b>Insulation resistance</b>           | > 10 MOhm for signalling circuit  |

## Environment

|  |  |
|--|--|
| <b>IP degree of protection</b>               | IP20 front face IEC 60529  |
| <b>Climatic withstand</b>                    | IACS E10<br>IEC 60947-1 Annex Q category D   |
| <b>Protective treatment</b>                  | TH IEC 60068-2-30  |
| <b>Pollution degree</b>                      | 3  |
| <b>Ambient air temperature for operation</b> | -40...140 °F (-40...60 °C)<br>140...158 °F (60...70 °C) with derating  |
| <b>Ambient Air Temperature for Storage</b>   | -76...176 °F (-60...80 °C)   |
| <b>Operating altitude</b>                    | 0...9842.52 ft (0...3000 m)  |
| <b>Fire resistance</b>                       | 1562 °F (850 °C) IEC 60695-2-1   |
| <b>Flame retardance</b>                      | V1 conforming to UL 94   |
| <b>Mechanical robustness</b>                 | Vibrations contactor open2 Gn, 5...300 Hz<br>Vibrations contactor closed4 Gn, 5...300 Hz<br>Shocks contactor open10 Gn for 11 ms<br>Shocks contactor closed15 Gn for 11 ms |
| <b>Height</b>                                | 3.9 in (99 mm)   |
| <b>Width</b>                                 | 3.5 in (90 mm)   |
| <b>Depth</b>                                 | 3.6 in (92 mm)   |
| <b>Net Weight</b>                            | 1.559 lb(US) (0.707 kg)  |

## Ordering and shipping details

|                          |                                    |
|--------------------------|------------------------------------|
| <b>Category</b>          | 22354-CTR, TESYS D, OPEN, 9-38A AC |
| <b>Discount Schedule</b> | I12                                |
| <b>GTIN</b>              | 00785901673606                     |
| <b>Returnability</b>     | No                                 |
| <b>Country of origin</b> | FR                                 |

## Packing Units

|                               |     |
|-------------------------------|-----|
| <b>Unit Type of Package 1</b> | PCE |
| <b>Nbr. of units in pkg.</b>  | 1   |

## Contractual warranty

|                             |    |
|-----------------------------|----|
| <b>Warranty (in months)</b> | 18 |
|-----------------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No