

## Data sheet for Sine-wave filter

Article No. : 6SL3202-0AE26-2SA0



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Rated data       |               |
|------------------|---------------|
| Number of phases | 3 AC          |
| Line voltage     | 380 ... 480 V |
| Rated current    | 61.8 A        |
| Power loss       | 0.152 kW      |

| Electrical data |          |
|-----------------|----------|
| Inductance      | 0.60 mH  |
| Capacitance     | 14.10 µF |

| Mechanical data      |                     |
|----------------------|---------------------|
| Degree of protection | IP00                |
| Net weight           | 34.00 kg (74.96 lb) |
| Dimensions           |                     |
| Width                | 250.0 mm (9.84 in)  |
| Height               | 305.0 mm (12.01 in) |
| Depth                | 262.0 mm (10.31 in) |

| Connections                   |                      |
|-------------------------------|----------------------|
| Power connection Power Module |                      |
| Version                       | screw-type terminal  |
| Conductor cross-section       | 50.00 mm² (AWG 1)    |
| Power connection motor        |                      |
| Version                       | screw terminals      |
| Conductor cross-section       | 50.00 mm² (AWG 1)    |
| Max. motor cable length       |                      |
| Shielded                      | 200.00 m (656.17 ft) |
| Unshielded                    | 300.00 m (984.25 ft) |
| PE connection                 |                      |
| Version                       | M6 screw             |

| Standards                  |       |
|----------------------------|-------|
| Certificate of suitability | cURus |